

Codice articolo

MHVN 16.32



Custodia mobile, serie LS-TYPE, con 4 piolini, ingresso cavo verticale M32, grandezza "77.27"

Descrizione prodotto

Tipo prodotto	Custodia mobile
Serie	LS-TYPE
Tipo chiusura	Con 4 piolini
Grandezza	Grandezza "77.27"
Ingresso cavo	Ingresso cavo verticale M32

Dati tecnici

Grado di protezione IP	IP65
-------------------------------	------

Ulteriori dettagli tecnici

Peso	126,00 g
Temperature di esercizio (min, max)	-40°C...+125°C

Proprietà dei materiali

Colore	Nero RAL 9005
Conformità RoHs	Conforme
China RoHs - EFUP	E
Sostanze REACH SVHC	No

Approvazioni / Normative

Certificazioni	DNV, BV
UL	ECBT2
cUL	ECBT8

Informazioni commerciali

Codice EAN13	8015747194280
Classificazione ecl@ss	27440202
Classificazione ETIM	EC000437

Caratteristiche imballaggio


Peso sottoimballo	0,63 kg
Descrizione sottoimballo	Termoretraibile
Quantità sottoimballo	5 pz
Codice EAN13 sottoimballo	8015747194297

Codice articolo

MHVN 16.32



Disegni da catalogo



Disegni da catalogo

CH..N - MA, MF..N enclosures

size "77.27"

LS-TYPE version

inserts:

CD	40 poles + @	49+52 *
CT, CTS **)	40 poles + @	56 *
CDD	72 poles + @	62+65 *
CDE	32 poles + @	82+84 *
CSH	16 poles + @	90+92 *
CCE	16 poles + @	98+102 *
CNE, CSE, JCNE, JCSE	16 poles + @	99 and 108 *
CSS	16 poles + @	120+122 *
CTE, CTSE **)	16 poles + @	128 *
CMSE	6+2 (aux) poles + @	137 *
CMCE	6+2 (aux) poles + @	136 *
CP	6 poles + @	149+150 *
CX	6/36 e 12/2 poles + @	152+153 *
CX	4/0 e 4/2 poles + @	154 *
MIXO	4 modules	160+195 *

insert centre distance: 77,5 x 27 mm

* refer to catalogue page CN.12

description

part no.

entry

M

bulkhead mounting housing, with 2 levers

CHIN 16

surface mounting housing, high construction, with 2 levers

MAPN 16.32

32

with pegs, side entry

with pegs, side entry, high construction

with pegs, top entry

with pegs, top entry, high construction

MHON 16.32

32

MFON 16.32

32

MHVN 16.32

32

MFVN 16.32

32

** only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

housings with double lever

hoods with 4 pegs

dimensions in mm

CHIN 16

MAPN 16.32

MHON 16.32

MFON 16.32

MHVN 16.32

MFVN 16.32

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.