

Codice articolo

TM 3265KIS



Presca con interruttore di blocco, serie TM, 3 poli + N + PE, 6 h (rosso), 32 A, 200/346 ÷ 240/415 V, portafusibile sezionabile 10 x 38 mm, con scatola base

Descrizione prodotto		Proprietà dei materiali	
Tipo prodotto	Presca con interruttore di blocco	Colore	Grigio RAL 7012, rosso RAL 3000
Serie	TM.. IS/KIS		Conforme con esenzioni
N. poli	3 poli + neutro + 	Conformità RoHs	6(c): lega di rame contenente fino al 4% in peso di piombo
Riferimento orario	6	China RoHs - EFUP	50
Grandezza	115 x 450 x 18 mm	Sostanze REACH SVHC	Si Piombo
Specifica	Portafusibile sezionabile 10 x 38 mm Con scatola base	Codice SCIP	Ce861c8d-b979-403b-96d9-80aef6dc281d
Dati tecnici		Approvazioni / Normative	
Corrente	32 A	Normativa di riferimento	EN 60309-1, -2 e -4
Tensione	200/346 ÷ 240/415 V	Informazioni commerciali	
Grado di protezione IP	IP66 / IP67	Codice EAN13	8015747126151
Ulteriori dettagli tecnici		Caratteristiche imballaggio	
Peso	1.695,00 g	Lunghezza imballo	385,00 mm
Temperature di esercizio (min, max)	-25°C ... +40°C	Altezza imballo	320,00 mm
Grado autoestinguenza UL 94	V-2	Profondità imballo	485,00 mm
Grado di protezione IK (urti)	IK10	Peso imballo	15,81 kg
		Volume imballo	59,75 dm ³
		Descrizione imballo	Scatola cartone
		Quantità imballo	9 pz
		Codice EAN13 imballo	8015747126946
		Peso sottoimballo	1,76 kg
		Descrizione sottoimballo	Vassoio cartone
		Quantità sottoimballo	1 pz
		Codice EAN13 sottoimballo	8015747126953

Codice articolo TM 3265KIS



Disegni da catalogo

TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier

- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (IK 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with $I_{n1} = 32A$ rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions 0 and 1
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

16A
IP66/IP67 degree of protection

32A
IP66/IP67 degree of protection

Poles	Frequency Hz	Voltage V	Earthing contact position h	Part No.	Colour	Part No.	Colour	
2P+⊕	50 and 60	100 - 130	4	TM 1643 IS ⊕	Yellow	TM 3243KIS ⊕	Yellow	
		200 - 250	6	TM 1663 IS ⊕	Blue	TM 3263KIS ⊕	Blue	
		380 - 415	9	TM 1693 IS ⊕	Red	TM 3293KIS ⊕	Red	
		480 - 500	7	TM 1673 IS ⊕	Black	TM 3273KIS ⊕	Black	
		ins. transformer	12	TM 16123 IS ⊕	A.V.	TM 32123KIS ⊕	A.V.	
		> 300 - 500	> 50	2	TM 1623 IS ⊕	Green	TM 3223KIS ⊕ (up to 400V)	Green
3P+⊕	50 and 60	100 - 130	4	TM 1644 IS ⊕	Yellow	TM 3244KIS ⊕	Yellow	
		200 - 250	9	TM 1694 IS ⊕	Red	TM 3294KIS ⊕	Red	
		380 - 415	6	TM 1664 IS ⊕	Blue	TM 3264KIS ⊕	Blue	
		440 - 460	11	TM 16114 IS ⊕	Black	TM 32114KIS ⊕	Black	
		480 - 500	7	TM 1674 IS ⊕	Black	TM 3274KIS ⊕	Black	
		380	3	TM 1634 IS ⊕	Red	TM 3234KIS ⊕	Red	
		440	3	TM 1634 IS ⊕	Red	TM 3234KIS ⊕	Red	
		100 - 300	> 50	10	TM 16104 IS ⊕	Green	TM 32104KIS ⊕ (up to 400V)	Green
		> 300 - 500	> 50	2	TM 1624 IS ⊕	Green	TM 3224KIS ⊕ (up to 400V)	Green
		3P+N+⊕	50 and 60	57/100 - 75/130	4	TM 1645 IS ⊕	Yellow	TM 3245KIS ⊕
120/208 - 144/250	9			TM 1695 IS ⊕	Red	TM 3295KIS ⊕	Red	
200/346 - 240/415	6			TM 1665 IS ⊕	Blue	TM 3265KIS ⊕	Blue	
277/480 - 288/500	7			TM 1675 IS ⊕	Black	TM 3275KIS ⊕	Black	
250/440 - 265/460	11			TM 16115 IS ⊕	Black	TM 32115KIS ⊕	Black	
220/380	3			TM 1635 IS ⊕	Red	TM 3235KIS ⊕	Red	
250/440	3			TM 1635 IS ⊕	Red	TM 3235KIS ⊕	Red	
> 300 - 500	> 50			2	TM 1625 IS ⊕	Green	TM 3225KIS ⊕ (up to 400V)	Green

Legend
A.V. = Colour according to voltage
*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz

Accessories for socket-outlet combinations

TM 1145 TB (page 24) with 1 plate
TM 1114 DB (page 26) with 2 plates
TM 1114 GB (page 27)

Accessories for assembly on control panels
QP V - QG V

page 31

Dimensions indicated are not binding and may be changed without prior notice.

dimensions in mm

Poles	A	B
2P+⊕	133	276
3P+⊕	135	276
3P+N+⊕	140	277

12

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.