



COLOR

- Black

MATERIAL

Neoprene

FIELD OF USE

Operating temperature:

-30°C ÷ 90°C

APPLICATION

- Abrasion resistance
- Resistant to low temperature
- Good resistance to oil and solvent
- Resistant to humidity and ageing

Technical data and packaging

CODE	DIMENSIONS				PACKAGING Bag pcs/bag
	Internal diameter (mm)	External diameter (mm)	Length (mm)	Wall thickness (NOM) (mm)	
5380	1,3	2,0	20	0,5	1000
5381	1,8	3,5	20	0,5	1000
5381BIS	2,4	4,5	20	0,6	1000
5382	2,5	5,5	25	0,9	1000
5383	3,0	6,0	25	0,6	1000
5384	4,0	8,0	30	1,2	1000
5385	5,0	9,0	25	0,7	1000
5386	7,5	12,0	30	0,8	1000
5387	10,0	15,0	35	0,9	500
5388	12,0	20,0	50	1,2	500
5389	14,0	23,0	50	1,3	500
5390	17,0	28,0	50	1,3	500

Mechanical features

PHYSICAL PROPERTIES			
Description	Test method	Typical value	UM
Tensile strength	ASTM D 638	>6,5	N/nm ²
Elongation at break	ASTM D 638	>500	%
Tear strength	-	>10	kN/m
Hardness shore A	-	40±5	-

ELECTRICAL PROPERTIES			
Description	Test method	Typical value	UM
Dielectric strength	ASTM D 149	>13	kV/mm
Volume resistivity	ASTM D 257	4X10 ⁹	W cm

THERMAL PROPERTIES			
Description	Test method	Typical value	UM
Flame resistance	UL94	V0	-
Short time operating temperature	-	110	°C