




Outside serrated cable ties with low profile head. Manufactured in polyamide 6.6, allow installation without any tool



## Technical Data

CODE	type	NOMINAL DIMENSIONS					BUNDLE DIAMETER	
		(mm) A	(mm) B	(mm) C	(mm) E	(mm) G	(mm) ø min	(mm) ø max
6501	A	200	8,8	1,7	14,7	6,7	15	40
6502	B	290	8,8	1,8	14,7	6,6	25	70
6503	B	380	8,8	1,8	14,7	6,6	25	100

## COLORS

- Black

## MATERIALS

**Material:** polyamide 6.6 + 1% carbon black

**Halogen free**

**Material flammability rating:**

UL 94-V2

**Excellent resistance to:** aromatic solvents, oils, greases and derivatives

**Good resistance to:** bases

**Limited resistance to:** acids

**Not resistant to:**

phenols and to chlorinated solvents

## APPLICATION

**Installation temperature:**

-10°C ÷ 60°C

**Working temperature:**

-40°C ÷ 85°C

## PRODUCTS CONFORMITY

**CE marking:** our products comply with the Low Voltage Directive 2014/35/EU and the cable ties are tested in accordance with CEI EN IEC 62275 "Cable management system – Cable ties for electrical installations".

**Type 1**

**REACH:** the materials used to produce the cable ties comply with 1907/2006/CE (REACH)

## PRODUCT CERTIFICATIONS:



Type Approval Certificate n. 13190/DO BV (reference standard IEC 62275, Bureau Veritas Rules for the classification of steel ship)

## Mechanical features and packaging

CODE	MECHANICAL FEATURES Newton (N) Tensile strength*	PACKAGING	
		(pcs) Bag	(pcs) Box
6501	400	100	4.000
6502	580	100	2.500
6503	580	100	2.000

\*Please consider a suitable safety factor equal or above 2