

**TECHNICAL DATA SHEET**

GREASE SPRAY WITH P.T.F.E.

Characteristics

Base:	Silicone grease with PTFE
Temperature of application:	-30 °C / + 220 °C (approximately)
Appearance:	translucent grease
Propellant:	Denatured and odourless hydrocarbon
Solvents Free, CFC free, Not Toxic	



Properties:

- It is a good penetrating grease
- High resistance to traction
- It prevents overheating and abrasion of the parts in contacts.
- Dielectric, isolating, protective.
- Water repellent (It can be used to lubricate underwater equipments)
- It contains PTFE that is a very good lubricant and penetrating agent.

Description

ELEMATIC GREASE SPRAY is used for general lubrication purposes.

It is used in mechanic industry especially to lubricate all mechanic parts where a good lubricant as silicone added with Ptf, is necessary.

Lubricant for chains and gear wheels, ball bearings and any other mechanic movement.

Instructions of use

Spray the product from 30 cm distance.

Packaging

Spray Aerosol ml 400

Box 25 Aerosol

Product Code **8242001**

Head office

ITW Construction Products Italy S.r.l.

Via Lombardia 10, 30030

Cazzago di Pianiga (VE)

Zona Industriale

e-mail: info@itw-italy.com

www.elematic.it