

0164010	<b>DATA SHEET</b>	
Valid from: 01.04.2019	<b>IEC extension cable KXN 9 L 2x1,5 round</b>	

## Application

The extension cable KXN 9 L 2 x 1,5 mm<sup>2</sup> is a PVC insulated cable which transmits the thermoelectric voltage of NiCr/Ni thermocouples. It is for flexible use and fixed installation in dry and damp rooms. They may only be installed outdoors with UV protection and in observation of the max. permitted temperature range.

## Design

Conductor	1.5 mm <sup>2</sup> (48 x 0.20 mm)	
Conductor material	KX alloying, accuracy class 2 according IEC 60584	
	Positive conductor:	NiCr (nickelchrome)
	Negative conductor:	Ni (nickel)
Core insulation	PVC compound	
Core identification	Positive conductor:	green
	Negative conductor:	white
Core layering	Cores twisted together	
Outer sheath	PVC compound, colour:	green

## Electrical properties

Limiting deviation class 2      ±100 µV (±2.5 °C) / measuring point temperature +900 °C

## Mechanical and thermal properties

Temperature range	occasional flexing:	-5 °C up to +70 °C
Minimum bending radius	occasional flexing:	12 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2	

Creator: TOME/PCM Released: ALTE/PDC	Document: DB0164010EN Version: 02	Page 1 of 1
---	--------------------------------------	-------------

We reserve all rights according to DIN ISO 16016.

PD 0019/05\_04.18EN