# 10190000 DATA SHEET Valid from: FRIC® U.R.E.4.55. (U.R.E.4.

# EPIC® H-BE 6 SS / H-BE 6 BS



### Description

17.08.2020

- Standard inserts with screw termination, crimp termination, cage clamp termination and Push-In termination
- The EPIC® H-BE series is suitable for applications that require a reliable connection when working with high voltages and currents
- Use for railway applications -Brand protection in rail vehicles: test according to EN 45545-2. Requirement sentences R22 and R23. Hazard levels HL1, HL2 and HL3.
- UL tested for applications in the control cabinet in accordance with UL 508 / UL 2237



#### General Characteristics

Series H-BE 6

Version Male/Female(Article 10191000)

Wire Protection Yes
Number of Contacts 6 + PE

Termination Methods Screw termination: 0.5 - 2.5 mm<sup>2</sup>

Protection (DIN EN 60529) IP65
Protection (NEMA 250, UL50E) 4, 12

Temperature Range -40°C to +100°C, short-term up to +125°C

#### **Mechanical Characteristics**

Cycle of mechanical operation 500

#### **Electrical Characteristics**

500 V Rated Voltage, IEC 600 V Rated Voltage, UL Rated Voltage, CSA 600 V Rated Impulse Voltage 6 kV Rated Current, IEC 16 A Rated Current, UL 16 A Rated Current, CSA 16 A < 2 mOhm **Contact Resistance** 

Degree of Soiling 3

#### **Materials and Surfaces**

Contacts Copper alloy, hard silver-plated

Insulating Body PC Flammability Class according to UL 94 V0

#### **Approvals**

UL-Approval, E-File-Number E75770 VDE-Approval, VDE-REG.-Nr. B437

#### Standard

Safety Standard IEC 61984, UL 1977

Creator: MANA2/PDP	Document: DB10190000EN	Page 1 of 2
Released: IVSE1/PDP	Version: 05	

# 10190000

# **DATA SHEET**


Valid from: 17.08.2020


EPIC® H-BE 6 SS / H-BE 6 BS




## **Technical Drawings**















Robust



Temperature-resistant

#### Info

Multifunctional insert for versatile appliactions Screw, crimp, cage clamp and Push-In version - freely combinable

## **Application range**

Mechanical engineering Light & sound technology Plastics industry

## Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP	Document: DB10190000EN	Page 2 of 2
Released: IVSE1/PDP	Version: 05	