

1026547	DATA SHEET	
valid from: 2021-03-03	ÖLFLEX® CHAIN 90 CP	

Application

ÖLFLEX® CHAIN 90 CP are shielded highly-flexible PUR single core cables approved for the European, North American and Canadian market, for permanent flexible use in power chains and fixed installation with narrow bending radii under increased mechanical load conditions. They are also suitable for use in dry, damp or wet areas. These products are suitable for outdoor use if the indicated temperature range is observed. ÖLFLEX® CHAIN 90 CP are increased resistant to oils and at room temperature largely resistant to acids and alkalis. The outer sheath withstands high mechanical stresses, in particular abrasion and dragging. It is also cut proof and resists microbes and hydrolysis. ÖLFLEX® CHAIN 90 CP are especially suitable for increased requirements (Extended Line) in power chains and in permanently moved machine parts. They are suitable for linear, automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted. The screening braid protects against interference from electrical fields.

Application range:

Power chains or moving machine parts, for wiring of electric and electronic equipment in switch cabinets, test systems in the automotive industry, vehicles and stationary fuel cell systems

USE acc. to RU: PUR sheathed cables for external wiring

USE acc. to cRU: Cables for internal or external interconnection with or without mechanical use.

Design

Design	acc. to UL AWM Style 11624, CSA C22.2 No. 210-15 and based on EN 50525-1
Certification	RU AWM 758, Style 11624 (File No. E63634) cRU AWM I A/B, II A/B (File No. E63634) DNV (Certificate no. TAE000047B)
Conductor	extra fine wire strands of bare copper acc. to IEC 60228 resp. EN 60228, Class 6
Insulation	Special compound based on TPE
Core identification code	Black
Screen	braid of tinned copper wires, coverage = 85 % (nominal value)
Outer sheath	TMPU Polyurethane compound (UL/CSA 80° C rating) colour: black, similar RAL 9005

Electrical properties at 20 °C

Nominal voltage	IEC U ₀ / U:	600/1000 V
Rated voltage	RU/ cRU:	1000 V
Test voltage		4000 V AC

Mechanical and thermal properties

Minimum bending radius	flexing: up from 7.5 x outer diameter fixed installation: 3 x outer diameter
Temperature range	flexing (EN): -35 °C up to +80 °C max. conductor temp. flexing (RU/cRU): up to +80 °C max. conductor temp. fixed installation (EN): -50 °C up to +80 °C max. conductor temp. fixed installation(RU/cRU): up to +80 °C max. conductor temp.
Bending cycles and power chain operation parameters	See Selection Table A2-1 in the appendix of our online catalogue For use in power chains: Please comply with assembly guideline Appendix T3
Torsional stress	TW-0 (5000 cycles at ≥ +5°C) TW-2 (2000 cycles at ≥ -40°C) ± 150 °/m at 1 rotation per minute
Flammability	flame retardant acc. to: IEC 60332-1-2 resp. EN 60332-1-2 IEC 60332-3-24 resp. EN 60332-3-24 IEC 60332-3-25 resp. EN 60332-3-25 RU: Vertical flame test VW-1 cRU: FT1
Halogen free	acc. to VDE 0472-815
UV resistance	acc. to EN 50618 EN 50620 EN ISO 4892-2-2013, method A (change of colour allowed)

Creator: PESA / PDC	Document: DB1026547EN	Page 1 of 2
Released: ALTE / PDC	Version: 04	

1026547	DATA SHEET	
valid from: 2021-03-03	ÖLFLEX® CHAIN 90 CP	

Ozone resistance	acc. to EN 50396, method B
Oil resistance	acc. to EN 50363-10-2
Tests	acc. to IEC 60811 resp. EN 60811, EN 50395, EN 50396 UL 1581 und CSA C22.2
General requirements	These cables are conform to the EU-Directives 2014/35/EU (Low Voltage Directive)
Environmental information	These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: PESA / PDC	Document: DB1026547EN	Page 2 of 2
Released: ALTE / PDC	Version: 04	