

21700537	<b>DATA SHEET</b>	
Valid from: 17.09.2018	<b>ED-CAN-90</b>	

## Description

- CAN-Bus Sub-D socket with screw connector, 9-pole
- For cable diameters 5.0 – 8.0 mm
- Small housing
- Easy to connect
- Metallized housing



## General characteristics

Programming/diagnostic interface	No
Cable outlet	90°
Connection type	Screwing
Interfaces	CAN-Bus-station: SUB-D socket, 9-pole CAN-Bus-cable: 6 terminals for wires up to 1.0 mm <sup>2</sup>
Pin assignment Sub-D	CAN Low = Pin 2 CAN High = Pin 7 CAN Gnd = Pin 3 GND = Pin 6 CAN V+ = Pin 9
Suitable cable-Ø	5.0 – 8.0 mm
Termination resistor	120 Ω integrated, connectable with slide switch
Transmission rate (max.)	1 Mbit/s
Temperature range	0 °C to +60 °C (32 °F to 140 °F) (operation) -25 °C to +80 °C (-13 °F to 176 °F) (storage/transportation)
Protection class	IP 20

## Mechanical characteristics

Dimensions	65 mm x 48 mm 16 mm (LxWxH)
Weight	Appr. 40 g

## Electrical characteristics

Pollution degree	2
------------------	---

## Application range

Automation, industrial machinery and plant engineering

## Note

Photographs are not true to scale and do not represent detailed images of the respective products.

Creator: MOKO2/PDP Released: IVSE1/PDP	Document: DB21700537EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------