


61803800	DATA SHEET	
Valid from: 26.11.2018	SILVYN® COMPACT M	

The SILVYN® COMPACT M is a conduit gland that provides optimum assembly conditions due to the compact dimensions. In combination with liquid-tight conduits (galvanized steel tube with coating), it forms an easy to install system with high protection degree.




Material:
 Body – Nickel plated brass
 Nut – Nickel plated brass
 Clamping ring – PA6
 Sleeve – galvanized steel
 O-ring – NBR

Features:
 High mechanical stress
 Corrosion resistant

Temperature range: -45°C up to +105 °C

Protection class: IP 67



Dimension table:

Part No.	NW	Thread	Thread length mm	Length mm	Inner Diameter mm	SW 1	SW 2	Weight Kg/100
6180 3800	3/8"	M16x1,5	10	31	11,0	26	24	3,9
6180 3801	3/8"	M20x1,5	10	31	11,0	26	24	4,0
6180 3802	1/2"	M20x1,5	10	32	14,5	29	27	4,4
6180 3803	3/4"	M25x1,5	10	33	19,4	35	33	6,6
6180 3804	1"	M32x1,5	12	36	24,7	45	42	11,7
6180 3805	1,1/4"	M40x1,5	13	40	33,3	53	50	16,0
6180 3806	1,1/2"	M50x1,5	14	46	38,0	62	58	25,3
6180 3807	2"	M63x1,5	16	52	49,0	76	72	38,6

Suitable conduits:
 SILVYN® HTDL
 SILVYN® EF
 SILVYN® OR
 SILVYN® HCX
 SILVYN® HFX

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB61803800EN Version: 04	Page 1 of 1
---	---------------------------------------	-------------