


Pendelleuchte | 220-240 V | 1xE27
12107



Technische Daten	
Typ	Oberfläche
Installationsposition	Decke
Installationsumgebung	Indoor
Leuchtmittel inbegriffen	Nein
Anschluss der Leuchte	1 x E27
Light emission direction	downward
Frequency	50-60 Hz
Optik	Diffuses
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	5.8 m
Harzbeschichtung	Nein
Nettogewicht	7.33 Kg

Oberfläche Oberfläche Gehäuse	
Material	PC
Farbe	Weiß
Oberfläche Oberfläche diffusor	
Material	PE
Farbe	Natural polyethilene
Oberfläche Oberfläche fassung	
Material	Eisen
Farbe	Weiß RAL 9010 Matt
Bearbeitungstyp	Lackierung

Pendelleuchte | 220-240 V | 1xE27

12107

Double emission pendant luminaires for indoor application. Compatibility: LED lamp; lamp cap 1xE27.

The device body is made of PC and features a white finish; the diffuser is made of pe; the mounting frame is made of iron, with a ral 9010 white matte finish, processed by means of coating.


The ingress protection degree is IP20; the total weight is of 7.33 kg.

The power supply cable is included and features a 5.8 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	79 %
Leuchten Lichtstrom	725 lm
Consumption	57 W
Leuchten Lichtausbeute	16 lm/W
Verbindungstemperatur (Leuchte)	80
Lichtstrom (Lichtquelle)	1 x lm
OPTICAL	
Optik C0/C180	180°
Light distribution simmetry	Symmetrical



Pendelleuchte | 220-240 V | 1xE27

12107

Double emission pendant luminaires for indoor application. Compatibility: LED lamp; lamp cap 1xE27.

The device body is made of PC and features a white finish; the diffuser is made of pe; the mounting frame is made of iron, with a ral 9010 white matte finish, processed by means of coating.

The ingress protection degree is IP20; the total weight is of 7.33 kg.

The power supply cable is included and features a 5.8 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.