


Pendelleuchte | 220-240 V
150 topLED 18 W DC - 20 W AC | CRI 90
16110



Technische Daten	
Typ	Oberfläche
Installationsposition	Decke
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward and upward
Lampe Nennleistung	18 W DC
Gesamtleistung	20 W
Lichtstrom (Lichtquelle)	2748 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	220 - 240 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP65
IK	IK10
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	2,7 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	4.9 Kg
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	Ja

Oberfläche Oberfläche Gehäuse	
Material	Eisen
Farbe	Weiß RAL 9010
Oberfläche Oberfläche diffusor	
Material	PE
Farbe	Natural polyethylene
Oberfläche Oberfläche fassung	
Material	Eisen
Farbe	Weiß RAL 9010
Cables Electrification+suspension	
Max. Kabellänge	2700 mm

Pendelleuchte | 220-240 V | 150 topLED 18 W DC - 20 W AC | CRI 90
16110

Double emission pendant luminaires for outdoor application. The warm white LED light source with a diffused light distribution is composed of 150 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2748 lm, with a 152.7 lm/W nominal luminous efficacy.


The device body is made of iron and features a white ral 9010 finish; the diffuser is made of pe; the mounting frame is made of iron, with a white ral 9010 finish.

The ingress protection degree is IP65; the total weight is of 4.9 kg.

The total absorbed power is 20 W The power supply cable is included and features a 2,7 m length.

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	76 %
Lichtstrom (Lichtquelle)	2748 lm
Leuchten Lichtstrom	2115 lm
Consumption	20 W
Leuchten Lichtausbeute	105 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	-20 / +50°C
LED Life / Failure Ratio	
L70 B10 C0 102000h (at Tj 115 Ta 25)	
L90 B10 C0 55000h	
UGR	
UGR axial	14.2
UGR transversal	16.3
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20
OPTICAL	
Optik C0/C180	180°
Light distribution simmetry	Symmetrical