


Pendelleuchte | 220-240 V | 1xE27
16170



Technische Daten	
Typ	Oberfläche
Installationsposition	Decke
Installationsumgebung	Outdoor
Leuchtmittel inbegriffen	Nein
Anschluss der Leuchte	1 x E27
Frequency	50-60 Hz
Optik	Diffuses
Isolierklasse	2
IP	IP65
IK	IK10
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	2.5 m
Harzbeschichtung	Nein
Nettogewicht	7.400 Kg

Oberfläche Oberfläche Gehäuse	
Material	Eisen
Farbe	Weiß RAL 9010
Oberfläche Oberfläche diffusor	
Material	PE
Farbe	Natural polyethilene
Oberfläche Oberfläche fassung	
Material	Eisen
Farbe	Weiß RAL 9010
Cables Pendelleuchte	
Max. Kabellänge	2500 mm

Pendelleuchte | 220-240 V | 1xE27
16170

Single emission pendant luminaires for outdoor application. Compatibility: LED lamp; lamp cap 1xE27.

The device body is made of iron and features a white ral 9010 finish; the diffuser is made of pe; the mounting frame is made of iron, with a white ral 9010 finish.


The ingress protection degree is IP65; the total weight is of 7.400 kg.

The power supply cable is included and features a 2.5 m length.

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	79 %
Leuchten Lichtstrom	1506 lm
Consumption	30 W
Leuchten Lichtausbeute	63 lm/W
Verbindungstemperatur (Leuchte)	80
Lichtstrom (Lichtquelle)	1 x 1m
OPTICAL	
Optik C0/C180	180°
Light distribution simmetry	Symmetrical



Pendelleuchte | 220-240 V | 1xE27

16170

Single emission pendant luminaires for outdoor application. Compatibility: LED lamp; lamp cap 1xE27.

The device body is made of iron and features a white ral 9010 finish; the diffuser is made of pe; the mounting frame is made of iron, with a white ral 9010 finish.

The ingress protection degree is IP65; the total weight is of 7.400 kg.

The power supply cable is included and features a 2.5 m length.

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.