

Systeme - Pendelleuchte | 220-240 V | 72 + 132 topLED 44 W DC - 48 W AC | CRI 92
60884W00

Double emission systems, pendant luminaires or pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 132 topLEDs with CCT of 3000 K and a CRI 92; the source luminous flux is 3699 lm, with a 168.1 lm/W nominal luminous efficacy The warm white LED light source with a diffused light distribution is composed of 72 topLEDs with CCT of 3000 K and a CRI 92; the source luminous flux is 2018 lm, with a 91.7 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text black ral9005 finish, processed by means of powder coating with thermosetting powders; the diffuser is made of PC; the diffuser is made with a satin finishing treatment.

The ingress protection degree is IP40; the total weight is of 3.3 kg.

The total absorbed power is 48 W The power supply cable is included and features a 2 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält 4.2 Lichtquellen der Energieeffizienzklasse E, E.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	58 %
Lichtstrom (Lichtquelle)	5717 lm
Leuchten Lichtstrom	3369 lm
Consumption	48 W
Leuchten Lichtausbeute	70 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	92 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 494435h (at Tj 65 Ta 25)
L80 B10 C0 310287h (at Tj 65 Ta 25)
L90 B10 C0 147586h (at Tj 65 Ta 25)

