


Systeme - Lineare Elemente
396 topLED 30 W DC 24 V | Modular | CRI 80
62472W



Technische Daten	
Typ	Systeme - Lineare Elemente - Frame
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Light emission direction	downward
Lampe Nennleistung	30 W DC
Lichtstrom (Lichtquelle)	4577 lm
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP40
IP optisches System	IP54
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Einbautiefe	13 mm
Typ Lichtabstrahlung	Einflammig
Nettogewicht	1.1 Kg
Modularity	Modular
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein
Optiktechnologie	Dot free

Oberfläche Oberfläche Gehäuse

Material	Aluminiumlegierung 6060
Farbe	Text white RAL9003
Bearbeitungstyp	Pulverbeschichtung mit duroplastischen Pulvern

Elektronik

	99331 On/Off Driver 198~264V AC / 176~275V DC 150 W
	99332 1-10V Controller
	99374 On/Off Driver 198~264V AC / 176~275V DC 75 W
	99787 DALI Controller 100~305V AC / 142~431V DC 240 W
	83062 DALI - Push and Simply Dim Controller 198~264V AC / V DC

Systeme - Lineare Elemente | 396 topLED 30 W DC 24 V | Modular | CRI 80 | + 62461
62472W

Single emission systems, lines or lines for indoor application. The warm white LED light source is composed of 396 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4577 lm, with a 152.6 lm/W nominal luminous efficacy.



The device body is made of aluminium alloy 6060 and features a text white ral9003 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP40; the total weight is of 1.1 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 30 W

The device features protection class III and can be ceiling-mounted, with a 67 x 1505 mm hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse

Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	43 %
Lichtstrom (Lichtquelle)	4577 lm
Leuchten Lichtstrom	1984 lm
Consumption	30 W
Leuchten Lichtausbeute	66 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 145600h (at Tj 65 Ta 25)

L80 B10 C0 92440h (at Tj 65 Ta 25)

L90 B10 C0 45500h (at Tj 65 Ta 25)

UGR

UGR axial	22.7
UGR transversal	23.3
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C90/C270	100°
Optik C0/C180	106°
Light distribution simmetry	Symmetrical 2 assis

Systeme - Lineare Elemente | 396 topLED 30 W DC 24 V | Modular | CRI 80 | + 62464
62472W

Single emission systems, lines or lines for indoor application. The warm white LED light source is composed of 396 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4577 lm, with a 152.6 lm/W nominal luminous efficacy.



The device body is made of aluminium alloy 6060 and features a text white ral9003 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP40; the total weight is of 1.1 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 30 W

The device features protection class III and can be ceiling-mounted, with a 67 x 1505 mm hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse	
Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse D.	

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	35 %
Lichtstrom (Lichtquelle)	4577 lm
Leuchten Lichtstrom	1615 lm
Consumption	30 W
Leuchten Lichtausbeute	53 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio	
L70 B10 C0 145600h (at Tj 65 Ta 25)	
L80 B10 C0 92440h (at Tj 65 Ta 25)	
L90 B10 C0 45500h (at Tj 65 Ta 25)	

UGR	
UGR axial	18.2
UGR transversal	19
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	72°
Optik C0/C180	78°
Light distribution simmetry	Symmetrical 2 assis

Systeme - Lineare Elemente | 396 topLED 30 W DC 24 V | Modular | CRI 80 | + 83356
62472W

Single emission systems, lines or lines for indoor application. The warm white LED light source is composed of 396 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4577 lm, with a 152.6 lm/W nominal luminous efficacy.



The device body is made of aluminium alloy 6060 and features a text white ral9003 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP40; the total weight is of 1.1 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 30 W

The device features protection class III and can be ceiling-mounted, with a 67 x 1505 mm hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse	
Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse D.	

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	46 %
Lichtstrom (Lichtquelle)	4577 lm
Leuchten Lichtstrom	2142 lm
Consumption	30 W
Leuchten Lichtausbeute	71 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio	
L70 B10 C0 145600h (at Tj 65 Ta 25)	
L80 B10 C0 92440h (at Tj 65 Ta 25)	
L90 B10 C0 45500h (at Tj 65 Ta 25)	

UGR	
UGR axial	18.6
UGR transversal	18.8
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	78°
Light distribution simmetry	Symmetrical

Systeme - Lineare Elemente | 396 topLED 30 W DC 24 V | Modular | CRI 80 | + 83407
62472W

Single emission systems, lines or lines for indoor application. The warm white LED light source is composed of 396 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4577 lm, with a 152.6 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text white ral9003 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP40; the total weight is of 1.1 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 30 W

The device features protection class III and can be ceiling-mounted, with a 67 x 1505 mm hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.


Energieeffizienzklasse	
Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse D.	

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	53 %
Lichtstrom (Lichtquelle)	4577 lm
Leuchten Lichtstrom	2439 lm
Consumption	30 W
Leuchten Lichtausbeute	81 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio	
L70 B10 C0 145600h (at Tj 65 Ta 25)	
L80 B10 C0 92440h (at Tj 65 Ta 25)	
L90 B10 C0 45500h (at Tj 65 Ta 25)	

UGR	
UGR axial	21.6
UGR transversal	23.9
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20


OPTICAL	
Optik C90/C270	106°
Optik C0/C180	114°
Light distribution simmetry	Symmetrical 2 assis




Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	1.33 1.53	E(0°) 3522 E(C90) 384 E(C0) 290
1.0	2.65 3.06	E(0°) 881 E(C90) 96 E(C0) 73
1.5	3.98 4.58	E(0°) 391 E(C90) 43 E(C0) 32
2.0	5.31 6.11	E(0°) 220 E(C90) 24 E(C0) 18
2.5	6.64 7.64	E(0°) 141 E(C90) 15 E(C0) 12
3.0	7.96 9.17	E(0°) 98 E(C90) 11 E(C0) 8

— C0/C180 (Half-peak divergence: 113.6°)
— C90/C270 (Half-peak divergence: 106.0°)

Rollip_PRO HI | Lines | Accessories
62472W

		Diffusor - Opaline diffuser L.5mt Diffusorart: opal diffuser. Material:Polymethylmethacrylat UV-beständige, farbe:Opal.	Code <u>62461</u>
		Diffusor - Opaline diffuser L.10mt Diffusorart: opal diffuser. Material:Polymethylmethacrylat UV-beständige, farbe:Opal.	Code <u>62462</u>
		Diffusor - Opaline diffuser L.20mt Diffusorart: opal diffuser. Material:Polymethylmethacrylat UV-beständige, farbe:Opal.	Code <u>62463</u>
		Diffusor - Blendfreier Diffusor – Länge 5m Diffusorart: anti-glare diffuser. Material:Polymethylmethacrylat UV-beständige, bearbeitungstyp :Satinieren.	Code <u>83356</u>
		Diffusor - Blendfreier Diffusor – Länge 10m Diffusorart: anti-glare diffuser. Material:Polymethylmethacrylat UV-beständige, bearbeitungstyp :Satinieren.	Code <u>83357</u>
		Diffusor - Opal – Länge 5 m Diffusorart: opal diffuser. Material:UV beständiges Polycarbonat, farbe:Opal.	Code <u>83407</u>
		Diffusor - Opal – Länge 10m Diffusorart: opal diffuser. Material:UV beständiges Polycarbonat, farbe:Opal.	Code <u>83408</u>
		Diffusor - Opal – Länge 20m Diffusorart: opal diffuser. Material:UV beständiges Polycarbonat, farbe:Opal.	Code <u>83409</u>

Rollip_PRO HI | Lines | Accessories
62472W



Endkappe - Quarzglas
Material:Stranggepresstes Aluminium EN AB - 46100, farbe:Text white RAL9003, bearbeitungstyp
:Pulverbeschichtung mit duroplastischen Pulvern.

Code
62460