

Systeme - Pendelleuchte | 220-240 V | 132 + 144 topLED 44 W DC - 46 W AC | CRI 92
62795N00

Double emission systems, pendant luminaires or pendant luminaires for indoor application. The natural white LED light source with a diffused light distribution is composed of 144 topLEDs with CCT of 4000 K and a CRI 92; the source luminous flux is 3331 lm, with a 151.4 lm/W nominal luminous efficacy The natural white LED light source with a diffused light distribution is composed of 132 topLEDs with CCT of 4000 K and a CRI 92; the source luminous flux is 3053 lm, with a 138.8 lm/W nominal luminous efficacy.



The device body is made of aluminium alloy 6060 and features a text black ral9005 finish, processed by means of powder coating with thermosetting powders; the diffuser is made of uv resistant polycarbonate.

The ingress protection degree is IP40;

The total absorbed power is 46 W The power supply cable is included and features a 2 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse

Dieses Produkt enthält 4.4 Lichtquellen der Energieeffizienzklasse E.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	57 %
Lichtstrom (Lichtquelle)	6384 lm
Leuchten Lichtstrom	3674 lm
Consumption	46 W
Leuchten Lichtausbeute	79 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	92 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 494435h (at Tj 65 Ta 25)

L80 B10 C0 310287h (at Tj 65 Ta 25)

L90 B10 C0 147586h (at Tj 65 Ta 25)

UGR

UGR axial	14.1
UGR transversal	16.2
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C90/C270	67°
Optik C0/C180	88°
Light distribution simmetry	Symmetrical 2 assis