


Systeme | 198-264 V
180 + 180 topLED 48 W DC - 54 W AC | Modular | CRI 80
64284W



Technische Daten	
Typ	Systeme
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Light emission direction	upward + downward
Lampe Nennleistung	48 W DC
Gesamtleistung	54 W
Lichtstrom (Lichtquelle)	8316 lm
Nominale Eingangsspannung	220 - 240 V AC
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP40
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Modularity	Modular
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	1 KV
Optiktechnologie	Dot free

Oberfläche Oberfläche Gehäuse	
Material	Aluminiumlegierung 6060
Farbe	Text white RAL9003
Bearbeitungstyp	Pulverbeschichtung mit duroplastischen Pulvern

Oberfläche Oberfläche diffusor	
Material	UV beständiges Polycarbonat
Farbe	Opal

Systeme | 198-264 V | 180 + 180 topLED 48 W DC - 54 W AC | Modular | CRI 80 | + 65208
64284W

Double emission systems for indoor application. The warm white LED light source is composed of 180 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4158 lm, with a 173.3 lm/W nominal luminous efficacy. The warm white LED light source is composed of 180 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4158 lm, with a 173.3 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text white ral9003 finish, processed by means of powder coating with thermosetting powders; the diffuser is made of uv resistant polycarbonate.

The ingress protection degree is IP40;

The total absorbed power is 54 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse

Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	62 %
Lichtstrom (Lichtquelle)	8316 lm
Leuchten Lichtstrom	5167 lm
Consumption	54 W
Leuchten Lichtausbeute	95 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 145600h (at Tj 65 Ta 25)

L80 B10 C0 92440h (at Tj 65 Ta 25)



L90 B10 C0 45500h (at Tj 65 Ta 25)

UGR

UGR axial	18.5
UGR transversal	20.8
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C90/C270	95°
Optik C0/C180	119°
Light distribution simmetry	Symmetrical 2 assis



Systeme | 198-264 V | 180 + 180 topLED 48 W DC - 54 W AC | Modular | CRI 80 | + 65236

64284W

Double emission systems for indoor application. The warm white LED light source is composed of 180 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4158 lm, with a 173.3 lm/W nominal luminous efficacy. The warm white LED light source is composed of 180 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4158 lm, with a 173.3 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text white ral9003 finish, processed by means of powder coating with thermosetting powders; the diffuser is made of uv resistant polycarbonate.

The ingress protection degree is IP40;

The total absorbed power is 54 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse

Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	57 %
Lichtstrom (Lichtquelle)	8316 lm
Leuchten Lichtstrom	4812 lm
Consumption	54 W
Leuchten Lichtausbeute	89 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 145600h (at Tj 65 Ta 25)

L80 B10 C0 92440h (at Tj 65 Ta 25)



L90 B10 C0 45500h (at Tj 65 Ta 25)

UGR

UGR axial	14.3
UGR transversal	16.4
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C90/C270	67°
Optik C0/C180	88°
Light distribution simmetry	Symmetrical 2 assis



Rollip7035_MP | Systems | Accessories
64284W



Hängeleuchten - Suspension kit 2 mt.
Material:Messing OT58, farbe:Text white RAL9003, bearbeitungstyp :Pulverbeschichtung mit duroplastischen Pulvern.

Code
64776



Diffusor - Opaline diffuser L.5mt
Diffusorart: opalen diffusor.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
65208



Diffusor - Opaline diffuser L.10mt
Diffusorart: opalen diffusor.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
65209



Diffusor - Opaline diffuser L.20mt
Diffusorart: opalen diffusor.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
65210



Diffusor - Opaline diffuser L.50mt
Diffusorart: opalen diffusor.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
65211



Diffusor - Blendschutzdiffusor UGR weniger als 19 – Länge 5 m
Diffusorart: anti-abbagliamento.
Material:UV beständiges Polycarbonat, farbe:Opal, bearbeitungstyp :Satinieren.

Code
65236



Diffusor - Blendschutzdiffusor UGR weniger als 19 – Länge 10m
Diffusorart: anti-abbagliamento.
Material:UV beständiges Polycarbonat, farbe:Opal, bearbeitungstyp :Satinieren.



Code
65237



Diffusor
Diffusorart: diffusore nero.
Material:UV beständiges Polycarbonat, farbe:Black.

Code
64045

Rollip7035_MP | Systems | Accessories
64284W

		<p>Diffusor</p> <p>Diffusorart: diffusore nero.</p> <p>Material:UV beständiges Polycarbonat, farbe:Black.</p>	<p>Code</p> <p>64055</p>
		<p>Diffusor</p> <p>Diffusorart: diffusore nero.</p> <p>Material:UV beständiges Polycarbonat, farbe:Black.</p>	<p>Code</p> <p>64065</p>
		<p>Diffusor</p> <p>Diffusorart: diffusore nero.</p> <p>Material:UV beständiges Polycarbonat, farbe:Black.</p>	<p>Code</p> <p>64075</p>
		<p>Endkappe - Endkappen-Kit für Rollip7035 - Weiß</p> <p>Material:Stranggepresstes Aluminium EN AB - 46100, farbe:Text white RAL9003, bearbeitungstyp :Pulverbeschichtung mit duroplastischen Pulvern.</p>	<p>Code</p> <p>64280</p>
		<p>Drahtabdeckung - Power-Kit - Doppelte Emission - On/off</p> <p>Material:Eisen, farbe:Text white RAL9003, bearbeitungstyp :Pulverbeschichtung mit duroplastischen Pulvern.</p>	<p>Code</p> <p>64649</p>