

Downlights | 6 x powerLEDs 12 W DC 630 mA | CRI 90

**64549N15**








270 x 90

| Technische Daten | |
|---|---|
| Installationsposition | Decke |
| Installationsumgebung | Indoor |
| Lichtquelle | LED |
| Circuit structure | powerLEDs |
| Optik | Spot |
| Light emission direction | downward |
| Lampe Nennleistung | 12 W DC |
| Lichtstrom (Lichtquelle) | 1422 lm |
| Eingangsspannungsbereich | 630mA |
| Ähnlichste Farbtemperatur / Tone | 4000 K |
| Farbwiedergabeindex | 90 Ra |
| Gleichstrom/Gleichspannung | CC |
| Isolierklasse | 3 |
| IP | IP20 |
| Glühdrahtprüfung | 850° |
| Direkte Montage auf normal entflammbaren Oberflächen | Ja |
| CE | Ja |
| Einschließlich Driver | Nein |
| Leuchte dimmbar | DALI - 1-10V |
| Schwenkbarkeit | Nein |
| Drehbarkeit | Nein |
| Begehbarkeit | Nein |
| Überrollbarkeit | Nein |
| Einschließlich Kabel | Ja |
| Kabellänge | 0.170 m |
| Harzbeschichtung | Nein |
| Einbautiefe | 71 mm |
| Typ Lichtabstrahlung | Einflammig |
| Nettogewicht | 0.690 Kg |
| Schutz vor elektrostatischen Entladungen | Nein |
| Schutz vor Stoßspannungen | Nein |
| Technische Merkmale des Produkts | TVS |

| Oberfläche Oberfläche Gehäuse | |
|---|---|
| Material | gesso |
| Farbe | Weiß |

| Oberfläche Oberfläche diffusor | |
|---|---|
| Material | ABS |
| Farbe | Weiß |

| Oberfläche Oberfläche strahler | |
|---|---|
| Material | Aluminiumlegierung 6060 |
| Farbe | Anodised black aluminium |
| Bearbeitungstyp | Anodisierung 15 µm |

**Elektronik**



99115
1-10V - N/O button Multi Power 198~264V AC / V DC (1 art.)



99105
On/Off Driver 198~264V AC (1 - 2 art.)



99129
On/Off Driver 198~264V AC (1 art.)



C-E100001
Push and Simply Dim - DALI-2 Multi Power 198~264V AC / V DC (1 - 2 art.)

| Cables Electrification | |
|---|---|
| Cable connector | No |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Downlights | 6 x powerLEDs 12 W DC 630 mA | CRI 90
**64549N15**

Single emission recessed downlights for indoor application. The natural white LED light source with a spot light distribution is composed of 6 powerled LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 1422 lm, with a 118.5 lm/W nominal luminous efficacy.

The device body is made of plaster and features a white finish; the diffuser is made of ABS.

The ingress protection degree is IP20; the total weight is of 0.690 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 12 W The power supply cable is included and features a 0.170 m length.

The device features protection class III and can be ceiling-mounted, with a 270 x 90 mm hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.


| **Energieeffizienzklasse** |
|---|
| Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse E. |


| **Illuminotechnical Eigenschaften** | |
|---|---|
| Light Output Ratio (LOR) | 57 % |
| Lichtstrom (Lichtquelle) | 1422 lm |
| Leuchten Lichtstrom | 817 lm |
| Consumption | 12 W |
| Leuchten Lichtausbeute | 68 lm/W |
| Farbtemperatur | 4000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Farbwiedergabeindex | 90 Ra |
| Standardumgebungstemperatur | -20 / +50°C |
| Typische Temperatur am Glas | 40°C |

| **LED Life / Failure Ratio** |
|---|
| L70 B10 C0 214455h (at Tj 65  Ta 25 ) |
| L80 B10 C0 136355h (at Tj 65  Ta 25 ) |
| L90 B10 C0 67466h (at Tj 65  Ta 25 ) |

| **UGR** | |
|---|---|
| UGR transversal | 5.8 |
| UGR axial | 4.7 |
| X=4H \| Y=8H | S=0.25H |
| Reflection factor | 70/50/20 |

| **OPTICAL** | |
|---|---|
| Optik C0/C180 | 12° |
| Light distribution simmetry | Symmetrical |







Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Gypsum Cell | Downlights | Accessories

**64549N15**






Dicken - KIT Dicken für die Montage auf Gipskarton

| Code |
| --- |
| 60830 |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.