Tour_D

Pendelleuchte | 336 topLED 75 W DC 24 V | CRI 80
65304W00



Technische Daten	
Typ	Oberfläche
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward and upward
Lampe Nennleistung	75 W DC
Lichtstrom (Lichtquelle)	9356 lm
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP40
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	Ja
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	5 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	6 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein
Optiktechnologie	Dot free

Oberfläche Oberfläche Gehäuse	
Material	Aluminiumlegierung 6060
Farbe	Burnished
Bearbeitungstyp	Flüssiglackierung

Oberfläche Oberfläche diffusor	
Material	UV beständiges Polycarbonat
Farbe	Opal

Elektronik

99332
1-10V Controller (1 - 2 art.)

99374
On/Off Driver 198~264V AC / 176~275V DC 75 W (1 art.)

99722
DALI Controller 90~305V AC / V DC (1 art.)

83062
DALI - Push and Simply Dim Controller 198~264V AC / V DC (1 - 2 art.)

83018
N/O button On/Off Driver 198~264V AC / 180~275V DC 75 W (- art.)

Cables Electrification	
Cable connector	No
Cable connector	No

Cables Pendelleuchte	
Max. Kabellänge	5000 mm

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Pendelleuchte | 336 topLED 75 W DC 24 V | CRI 80
65304W00

Double emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 336 topled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 9356 lm, with a 124.7 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a burnished finish, processed by means of liquid painting; the diffuser is made of uv resistant polycarbonate.

The ingress protection degree is IP40; the total weight is of 6 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 75 W The power supply cable is included and features a 5 m length.

The device features protection class III and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält 16 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	56 %
Lichtstrom (Lichtquelle)	9356 lm
Leuchten Lichtstrom	5249 lm
Consumption	75 W
Leuchten Lichtausbeute	69 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B10 C0 494435h (at Tj 65 Ta 25)
L80 B10 C0 310287h (at Tj 65 Ta 25)
L90 B10 C0 147856h (at Tj 65 Ta 25)

UGR	
UGR axial	15.9
UGR transversal	16
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	115°
Light distribution simmetry	Symmetrical

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Tour_D | Pendant Luminaires | Accessories
65304W00



Hängeleuchten - Befestigungssatz
Material:Aluminiumlegierung 6026, farbe:Burnished, bearbeitungstyp :Flüssiglackierung.

Code
64673




Deckenrosette - On/off - Max 75+75W
Einschließlich Driver: Ja; Netzteil-Verwaltungsprotokoll: On/off; Maximale Leistung: 75+75W.
Material:Eisen, farbe:Burnished, bearbeitungstyp :Flüssiglackierung.

Code
65332




Deckenrosette - DALI - Max 75+75W
Einschließlich Driver: Ja; Netzteil-Verwaltungsprotokoll: Dali; Maximale Leistung: 75+75W.
Material:Eisen, farbe:Burnished, bearbeitungstyp :Flüssiglackierung.

Code
65333




Deckenrosette - On/off - Max 450W - Fix 3x Tour
Einschließlich Driver: Ja; Netzteil-Verwaltungsprotokoll: On/off; Maximale Leistung: 450W.
Material:Eisen, farbe:Burnished, bearbeitungstyp :Flüssiglackierung.

Code
65416




Deckenrosette - DALI - Max 450W - Fix 3x Tour
Einschließlich Driver: Ja; Netzteil-Verwaltungsprotokoll: Dali; Maximale Leistung: 450W.
Material:Eisen, farbe:Burnished, bearbeitungstyp :Flüssiglackierung.

Code
65349



Schallabsorbierende Platte
Außendurchmesser: 665 mm D=31mm.
Farbe:Black.

Code
99959



Schallabsorbierende Platte
Außendurchmesser: 665 mm D=31mm.
Farbe:Hellgrau.

Code
99957

Schallabsorbierende Platte
Außendurchmesser: 665 mm D=31mm.
Farbe:Anthrazit.

Code
99958

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.