


Systeme | 180 topLED 27 W DC 24 V | CRI 92
65463W00



76 x
1510

Technische Daten	
Typ	Systeme
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	27 W DC
Lichtstrom (Lichtquelle)	3096 lm
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	92 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP40
IP optisches System	IP54
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	0.20 m
Harzbeschichtung	Nein
Einbautiefe	86 mm
Typ Lichtabstrahlung	Einflammig
Nettogewicht	1.70 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein
Optiktechnologie	Dot free

Oberfläche Oberfläche Gehäuse

Material	Aluminiumlegierung 6060
Farbe	Text white RAL9003
Bearbeitungstyp	Pulverbeschichtung mit duroplastischen Pulvern

Oberfläche Oberfläche diffusor

Material	UV beständiges Polycarbonat
Farbe	Opal

Elektronik

99331	On/Off Driver 198~264V AC / 176~275V DC 150 W (1 - 5 art.)
-------	--

99332	1-10V Controller (1 - 5 art.)
-------	-------------------------------

99374	On/Off Driver 198~264V AC / 176~275V DC 75 W (1 - 2 art.)
-------	---

99787	DALI Controller 100~305V AC / 142~431V DC 240 W (1 - 8 art.)
-------	--

83062	DALI - Push and Simply Dim Controller 198~264V AC / V DC (1 - 5 art.)
-------	---

Cables Electrification

Cable connector	No
-----------------	----

Systeme | 180 topLED 27 W DC 24 V | CRI 92
65463W00

Single emission systems for indoor application. The warm white LED light source with a diffused light distribution is composed of 180 topLEDs with CCT of 3000 K and a CRI 92; the source luminous flux is 3096 lm, with a 114.7 lm/W nominal luminous efficacy.



The device body is made of aluminium alloy 6060 and features a text white ral9003 finish, processed by means of powder coating with thermosetting powders; the diffuser is made of uv resistant polycarbonate.

The ingress protection degree is IP40; the total weight is of 1.70 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 27 W The power supply cable is included and features a 0.20 m length.

The device features protection class III and can be ceiling-mounted, with a 76 x 1510 mm hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse

Dieses Produkt enthält 3 Lichtquellen der Energieeffizienzklasse E.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	64 %
Lichtstrom (Lichtquelle)	3096 lm
Leuchten Lichtstrom	2004 lm
Consumption	30 W
Leuchten Lichtausbeute	66 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	92 Ra
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio

L70 B10 C0 494435h (at Tj 65 Ta 25)

L80 B10 C0 310287h (at Tj 65 Ta 25)

L90 B10 C0 147586h (at Tj 65 Ta 25)

UGR

UGR axial	21.7
UGR transversal	24.1
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C90/C270	100°
Optik C0/C180	123°
Light distribution simmetry	Symmetrical 2 assis