

Systeme | 198-264 V AC /220-240 V DC | 180 topLED 24 W DC - 27 W AC | Modular | CRI

92

65532M

Single emission systems for indoor application. The super warm white LED light source is composed of 180 topLED LEDs with CCT of 2700 K and a CRI 92; the source luminous flux is 3320 lm, with a 138.3 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text black ral9005 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP40; the total weight is of 3.5 kg.

The total absorbed power is 27 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse

Dieses Produkt enthält 3 Lichtquellen der Energieeffizienzklasse E.

Illuminotechnical Eigenschaften

Lichtstrom (Lichtquelle)	3320 lm
Farbtemperatur	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	92 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 494435h (at Tj 65 Ta 25)


L80 B10 C0 310287h (at Tj 65 Ta 25)

L90 B10 C0 147586h (at Tj 65 Ta 25)

Rollip60_MS | Systems | Accessories
65532M

		Diffusor - Opaldiffusor für Rollip60 L.5mt Diffusorart: opalen diffusor. Material:UV beständiges Polycarbonat, farbe:Opal.	Code 64297
		Diffusor - Opaldiffusor für Rollip60 L.10mt Diffusorart: opalen diffusor. Material:UV beständiges Polycarbonat, farbe:Opal.	Code 64298
		Diffusor - Opaldiffusor für Rollip60 L.20mt Diffusorart: opalen diffusor. Material:UV beständiges Polycarbonat, farbe:Opal.	Code 64299
		Diffusor - Anti-glare diffuser UGR less then 19, L.10mt Diffusorart: anti-abbagliamento. Material:UV beständiges Polycarbonat, farbe:Opal, bearbeitungstyp :Satinieren.	Code 64699
		Diffusor - Anti-glare diffuser UGR less then 19, L.5mt Diffusorart: anti-abbagliamento. Material:UV beständiges Polycarbonat, farbe:Opal, bearbeitungstyp :Satinieren.	Code 64698
		Diffusor Diffusorart: diffusore nero. Material:UV beständiges Polycarbonat, farbe:Black.	Code 64006
		Diffusor Diffusorart: diffusore nero. Material:UV beständiges Polycarbonat, farbe:Black.	Code 64016
		Diffusor Diffusorart: diffusore nero. Material:UV beständiges Polycarbonat, farbe:Black.	Code 64026

Rollip60_MS | Systems | Accessories
65532M



Endkappe
Material:Stranggepresstes Aluminium EN AB - 46100, farbe:Text black RAL9005, bearbeitungstyp
:Pulverbeschichtung mit duroplastischen Pulvern.

Code
99982