Node System_SP

Systeme | 1 arrayLED 5 W DC 48 V | CRI 92
76420W15



Technische Daten	
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	arrayLED
Optik	Spot
Light emission direction	downward
Lampe Nennleistung	5 W DC
Lichtstrom (Lichtquelle)	621 lm
Eingangsspannungsbereich	105mA
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	92 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP40
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
C.V. - C.C. Converter	48 V Konverter enthalten
Leuchte dimmbar	Ja
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.569 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Farbe	Text white RAL9003
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor	
Material	PC
Farbe	Transparent

Elektronik

99784
Switching Driver 180~295V AC / V DC (- art.)

99785
On/Off Driver 100~305V AC / V DC (- art.)

83256
On/Off Driver 220~240V AC 96 W (- art.)

83258
On/Off Driver 220~240V AC 96 W (- art.)

83260
On/Off Driver 100~305V AC / 142~431V DC 150 W (- art.)

83262
On/Off Driver 100~305V AC / 142~431V DC 150 W (- art.)

83264
On/Off Driver 100~305V AC / 142~431V DC 240 W (- art.)

83266
On/Off Driver 100~305V AC / 142~431V DC 240 W (- art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 1 arrayLED 5 W DC 48 V | CRI 92
76420W15

Single emission systems for indoor application. The warm white LED light source with a spot light distribution is composed of 1 arrayled LEDs with CCT of 3000 K and a CRI 92; the source luminous flux is 621 lm, with a 124.2 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a text white ral9003 finish, processed by means of coating; the diffuser is made of PC.

The ingress protection degree is IP40; the total weight is of 0.569 kg.

The total absorbed power is 5 W

The device features protection class III.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	109 %
Lichtstrom (Lichtquelle)	621 lm
Leuchten Lichtstrom	679 lm
Consumption	5 W
Leuchten Lichtausbeute	135 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Farbwiedergabeindex	92 Ra
Verbindungstemperatur (Leuchte)	80
Black Body Locus	On
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B10 C0 102000h (at Tj 65 Ta 25)
L90 B10 C0 55000h

UGR	
UGR axial	17.4
UGR transversal	16.4
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	16°
Light distribution simmetry	Symmetrical





COLOR VECTOR GRAPHIC





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Node System_SP | Systems | Accessories
76420W15



Drahtabdeckung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83254



Endkappe
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83295

Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83281



Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83275



Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83271



Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
C-U500010

Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83279

Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83277

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Node System_SP | Systems | Accessories
76420W15



Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83273



Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
C-U500012

Endkappe
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83287



Kabelverbindung
Typ linear.
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83291



Kabelverbindung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83283



Kabelverbindung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83285



Kabelverbindung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
C-U500008



Endkappe
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83293

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Node System_SP | Systems | Accessories
76420W15

		Code
	Lochschablone	83269

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.