# RollipPRO_C HI

Systeme | 396 topLED 30 W DC 24 V | CRI 80
**77467N00**




| Technische Daten | |
|---|---|
| Typ | Systeme |
| Installationsposition | Decke |
| Installationsumgebung | Indoor |
| Lichtquelle | LED |
| Circuit structure | topLED |
| Optik | Diffuses |
| Light emission direction | downward |
| Lampe Nennleistung | 30 W DC |
| Lichtstrom (Lichtquelle) | 4673 lm |
| Ähnlichste Farbtemperatur / Tone | 4000 K |
| Farbwiedergabeindex | 80 Ra |
| Gleichstrom/Gleichspannung | CV |
| Isolierklasse | 3 |
| IP | IP40 |
| IP optisches System | IP54 |
| Glühdrahtprüfung | 850° |
| Direkte Montage auf normal entflammbaren Oberflächen | Ja |
| CE | Ja |
| Einschließlich Driver | Nein |
| Leuchte dimmbar | DALI - 1-10V |
| Schwenkbarkeit | Nein |
| Drehbarkeit | Nein |
| Begehbarkeit | Nein |
| Überrollbarkeit | Nein |
| Einschließlich Kabel | Nein |
| Harzbeschichtung | Nein |
| Einbautiefe | 13 mm |
| Typ Lichtabstrahlung | Einflammig |
| Nettogewicht | 1.13 Kg |
| Schutz vor elektrostatischen Entladungen | Nein |
| Schutz vor Stoßspannungen | Nein |
| Optiktechnologie | Dot free |

| Oberfläche Oberfläche Gehäuse | |
|---|---|
| Material | Aluminiumlegierung 6060 |
| Farbe | Text white RAL9003 |
| Bearbeitungstyp | Pulverbeschichtung mit duroplastischen Pulvern |

| Oberfläche Oberfläche diffusor | |
|---|---|
| Material | Polymethylmethacrylat UV-beständige |
| Bearbeitungstyp | Satinieren |

**Elektronik**

99331
On/Off Driver 198~264V AC / 176~275V DC 150 W (1 - 5 art.)

99332
1-10V Controller (1 - 5 art.)

99374
On/Off Driver 198~264V AC / 176~275V DC 75 W (1 - 2 art.)

83333
Push and Simply Dim - DALI-2 Controller (1 - 5 art.)

C-E400002
Push and Simply Dim - DALI-2 Controller (1 - 8 art.)



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 396 topLED 30 W DC 24 V | CRI 80
**77467N00**

Single emission systems for indoor application. The natural white LED light source with a diffused light distribution is composed of 396 topled LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 4673 lm, with a 155.8 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text white ral9003 finish, processed by means of powder coating with thermosetting powders; the diffuser is made of uv resistant polymethylmethacrylate with a satin finishing treatment.

The ingress protection degree is IP40; the total weight is of 1.13 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 30 W

The device features protection class III and can be ceiling-mounted, with a 67 x 1508 mm hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.







| Energieeffizienzklasse |
|---|
| Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse D. |

| Illuminotechnical Eigenschaften | |
|---|---|
| Light Output Ratio (LOR) | 54 % |
| Lichtstrom (Lichtquelle) | 4673 lm |
| Leuchten Lichtstrom | 2554 lm |
| Consumption | 30 W |
| Leuchten Lichtausbeute | 85 lm/W |
| Farbtemperatur | 4000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Farbwiedergabeindex | 80 Ra |
| Standardumgebungstemperatur | -20 / +50°C |
| Typische Temperatur am Glas | 40°C |

| LED Life / Failure Ratio |
|---|
| L70 B10 C0 494435h (at Tj 65 Ta 25 ) |
| L80 B10 C0 310287h (at Tj 65 Ta 25 ) |
| L90 B10 C0 147586h (at Tj 65 Ta 25 ) |

| UGR | |
|---|---|
| UGR axial | 21.8 |
| UGR transversal | 24 |
| X=4H \| Y=8H | S=0.25H |
| Reflection factor | 70/50/20 |

| OPTICAL | |
|---|---|
| Optik C90/C270 | 106° |
| Optik C0/C180 | 114° |
| Light distribution simmetry | Symmetrical 2 assis |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.