
Xilema_W1

Wandleuchten | 220-240 V
topLED 20 W DC - 25 W AC | CRI 90
7778





Technische Daten	
Jahr der Verwirklichung	2014
Typ	Oberfläche
Installationsposition	Wand
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Double Asymmetric
Light emission direction	backward
Lampe Nennleistung	20 W DC
Gesamtleistung	25 W
Lichtstrom (Lichtquelle)	2556 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	220 - 240 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP20
IP optisches System	IP40
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Touch 5%-100%
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Steckdose	Type C
Kabellänge	3 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	2.565 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Farbe	Polished aluminium

Oberfläche Oberfläche diffusor	
Material	PMMA
Bearbeitungstyp	Sandstrahlen

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Wandleuchten | 220-240 V | topLED 20 W DC - 25 W AC | CRI 90
7778

Single emission wall lights for indoor application. The warm white LED light source with a double asymmetric light distribution is composed of 80 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2556 lm, with a 127.8 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a polished aluminium finish; the diffuser is made of pmma with a sandblasting treatment.

The ingress protection degree is IP20; the total weight is of 2.565 kg.

The total absorbed power is 25 W The power supply cable is included and features a 3 m length.

The device features protection class II and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.


Energieeffizienzklasse
Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse E.


Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	57 %
Lichtstrom (Lichtquelle)	2556 lm
Leuchten Lichtstrom	1459 lm
Consumption	25 W
Leuchten Lichtausbeute	58 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	25°C

LED Life / Failure Ratio
L70 B10 C0 100000h
L80 B20 C0 80000h
L90 B10 C0 60000h

UGR	
UGR axial	27.5
UGR transversal	27.8
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	135°
Optik C0/C180	155°
Light distribution simmetry	Symmetrical 2 assis





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.