
Pendelleuchte - Industriebeleuchtung
198-264 V AC /180-275 V DC | arrayLED 120 W DC - 130 W AC | CRI 80
80537C30







Technische Daten	
Typ	Oberfläche - Industriebeleuchtung
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	arrayLED
Optik	Medium Flood
Light emission direction	downward
Lampe Nennleistung	120 W DC
Gesamtleistung	130 W
Lichtstrom (Lichtquelle)	18723 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	198 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	5000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP65
IK	IK08
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	DALI
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	1 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	6.5 Kg
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	5 KV

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Farbe	grau Zirkonium
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor	
Material	Glas
Farbe	Transparent

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Pendelleuchte - Industriebeleuchtung | 198-264 V AC /180-275 V DC | arrayLED 120 W DC - 130 W AC | CRI 80

80537C30

Energieeffizienzklasse
Dieses Produkt enthält 3 Lichtquellen der Energieeffizienzklasse E.

Single emission pendant luminaires for indoor application. The cold white LED light source with a medium flood light distribution is composed of 3 arrayled LEDs with CCT of 5000 K and a CRI 80; the source luminous flux is 18723 lm, with a 156.0 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a grey zirconium finish, processed by means of coating; the diffuser is made of glass.

The ingress protection degree is IP65; the total weight is of 6.5 kg.

The total absorbed power is 130 W The power supply cable is included and features a 1 m length.

The device features protection class I and can be ceiling-mounted.


Compliant with the EN 60598-1 standard and its specific provisions.


Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	87 %
Lichtstrom (Lichtquelle)	18723 lm
Leuchten Lichtstrom	16317 lm
Consumption	130 W
Leuchten Lichtausbeute	125 lm/W
Farbtemperatur	5000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Gamut Area Index	55 GAI
Colour Rendering Index	10 R9
IES TM-30 Rf	83
IES TM-30 Rg	96
Black Body Locus	On
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	45°C


LED Life / Failure Ratio
L70 B10 C0 336810h (at Tj 65 Ta 25)


UGR	
UGR axial	17.5
UGR transversal	17.5
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	36°
Light distribution simmetry	Symmetrical









Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Flamp | Industrial Lighting | Accessories
80537C30



Diffusor - Mikroprismatischer Diffusor
Diffusorart: micro-prismatico.
Material:UV beständiges Polycarbonat.

Code
98727

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.