


Pendelleuchte | 220-240 V
topLED 86 W DC - 91 W AC | CRI 90
8110



Technische Daten	
Designer	Pio e Tito Toso
Jahr der Verwirklichung	2016
Typ	Oberfläche
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	upward
Lampe Nennleistung	86 W DC
Gesamtleistung	91 W
Lichtstrom (Lichtquelle)	8676 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	220 - 240 V AC
Frequency	60 - 50 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	DALI - PUSH DIM
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	5 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	6,330 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse

Material	Aluminium
Farbe	Text white RAL9003
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor

Material	PC
Farbe	Transparent

Oberfläche Oberfläche fassung

Material	Metall
Farbe	Text white RAL9003
Bearbeitungstyp	Lackierung

Cables Pendelleuchte

Max. Kabellänge	5000 mm
-----------------	---------

Pendelleuchte | 220-240 V | topLED 86 W DC - 91 W AC | CRI 90
8110

Single emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 54 topLED LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 8676 lm, with a 100.9 lm/W nominal luminous efficacy.


The device body is made of aluminium and features a text white ral9003 finish, processed by means of coating; the diffuser is made of PC; the mounting frame is made of metal, with a text white ral9003 finish, processed by means of coating.

The ingress protection degree is IP20;

The total absorbed power is 91 W The power supply cable is included and features a 5 m length.


The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse	
Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse F.	
Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	84 %
Lichtstrom (Lichtquelle)	8676 lm
Leuchten Lichtstrom	7345 lm
Consumption	91 W
Leuchten Lichtausbeute	80 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	25°C
LED Life / Failure Ratio	
L70 B10 C0 102000h	
L90 B10 C0 55000h	
OPTICAL	
Optik C90/C270	117°
Optik C0/C180	150°
Light distribution simmetry	Symmetrical 2 assis

Quad_P9 | Pendant Luminaires | Accessories
8110



Dimmer - 0-10V, 1-10V oder DALI-Dimmschnittstelle
Bluetooth, 220-240V

Code
KIT0079