Poller & Mastaufsatzleuchten | 200-264 V
18 topLED 10.8 W DC - 12 W AC | CRI 90
81104W00



Technische Daten	
Typ	Poller & Mastaufsatzleuchten
Installationsposition	Boden
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	10.8 W DC
Gesamtleistung	12 W
Lichtstrom (Lichtquelle)	1350 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	200 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP65
IK	IK07
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Emissione radiale
Nettogewicht	2.620 Kg
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	1 KV

Oberfläche Oberfläche Gehäuse	
Material	Edelstahl --
Farbe	Stahl

Oberfläche Oberfläche diffusor	
Material	PE
Farbe	Natural polyethilene

Oberfläche Oberfläche fassung	
Material	Edelstahl --
Farbe	Stahl

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Poller & Mastaufsatzleuchten | 200-264 V | 18 topLED 10.8 W DC - 12 W AC | CRI 90
81104W00

Radial diffusion bollard & pole for outdoor application. The warm white LED light source with a diffused light distribution is composed of 18 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1350 lm, with a 125.0 lm/W nominal luminous efficacy.

The device body is made of stainless steel and features a steel finish; the diffuser is made of pe; the mounting frame is made of stainless steel, with a steel finish. The robust steel structure enhances the fixture’s design and ensures long?lasting performance, even in the most demanding environments.

The ingress protection degree is IP65; the total weight is of 2.620 kg.

The total absorbed power is 12 W

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	42 %
Lichtstrom (Lichtquelle)	1350 lm
Leuchten Lichtstrom	580 lm
Consumption	12 W
Leuchten Lichtausbeute	48 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B10 C0 102000h
L90 B10 C0 55000h

UGR	
UGR axial	17.2
UGR transversal	17.6
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	106°
Optik C90/C270	102°
Light distribution simmetry	Symmetrical 2 assis

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Bond_Pro | Bollard & Pole | Accessories
81104W00



Erdspießen

installationsposition: terreno,Material Verkleidung: uv beständiges polycarbonat

Code

14931

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.