

Lineare Elemente - Effekte | 100-277 V | 30 x powerLEDs 37.4 W DC - 44 W AC | CRI 80
81706N20

Single emission lines for outdoor application. The natural white LED light source with a flood light distribution is composed of 30 powered LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 5850 lm, with a 156.4 lm/W nominal luminous efficacy.



The device body is made of aluminium alloy 6060 and features a anodised aluminium finish, processed by means of 20 µm anodizing. Surface treatment of the product body with chemical conversion of aluminum, designed to ensure maximum long-term resistance.

The ingress protection degree is IP66; the total weight is of 1.6 kg.

The total absorbed power is 44 W The power supply cable is included and features a 0.250 m length.

The device features protection class II and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse

Dieses Produkt enthält 5 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	62 %
Lichtstrom (Lichtquelle)	5850 lm
Leuchten Lichtstrom	3640 lm
Consumption	44 W
Leuchten Lichtausbeute	82 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	1.5 Step
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 1240219h (at Tj 65 Ta 25)

L80 B10 C0 745627h (at Tj 65 Ta 25)

L90 B10 C0 309367h (at Tj 65 Ta 25)

UGR

UGR axial	24.7
UGR transversal	30.6
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C90/C270	28°
Optik C0/C180	116°
Light distribution simmetry	Symmetrical 2 assis

Xenia_W Pro | Effects | Accessories
81706N20

	Klammer installationsposition: wand, decke, boden L=95.6mm, H=45mm, D=28mm. Material:Stahl AISI 304, farbe:Scotch Brite Stahl. Code <u>89045</u>
	Klammer installationsposition: wand, decke, boden L=155.6mm, H=45mm, D=28mm. Material:Stahl AISI 304, farbe:Scotch Brite Stahl. Code <u>89046</u>
	Klammer installationsposition: wand, decke, boden L=305.6mm, H=60mm, D=28mm. Material:Stahl AISI 304, farbe:Scotch Brite Stahl. Code <u>89047</u>
	Klammer installationsposition: wand, decke, boden L=35mm, H=72.8mm, D=36.5mm. Material:Stahl AISI 304, farbe:Scotch Brite Stahl. Code <u>98949</u>
	Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 5m) Länge 5000 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun. Code <u>89190</u>
	Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 5m) Länge 5000 mm; isolierung doppio; kabelklemme: nein. Code <u>98149</u>
	Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 10m) Länge 10000 mm; isolierung doppio; kabelklemme: nein. Code <u>89188</u>
	Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 1,5m) Länge 1500 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun. Code <u>99216</u>

Xenia_W Pro | Effects | Accessories
81706N20



Kabel und Stecker - Verlängerungskabel
Länge 1000 mm; isolierung doppio; kabelklemme: nein.

Code
98437



Blendschutz - Blendschutzblende
Blendschutzart: palpebra.
Material:Aluminiumlegierung 6060, farbe:Anodised aluminium, bearbeitungstyp :Anodisierung 20 µm.

Code
99778