



Wandleuchten | 220-240 V | topLED 7 W DC - 8 W AC

CRI 80

8406



Technische Daten	
Typ	Oberfläche
Installationsposition	Wand - Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	7 W DC
Gesamtleistung	8 W
Lichtstrom (Lichtquelle)	1022 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	220 - 240 V AC
Frequency	60 - 50 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP44
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Nein
Schwenkbarkeit	Orientabile
Gesamtwinkel (horizontale Ebene)	360 °
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	0.545 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Eisen
Farbe	Polished (galvanic) chrome
Bearbeitungstyp	Tampongalvanisieren
Oberfläche Oberfläche diffusor	
Material	PC
Farbe	Opal
Oberfläche Oberfläche fassung	
Material	Eisen
Farbe	Polished (galvanic) chrome
Bearbeitungstyp	Tampongalvanisieren

Wandleuchten | 220-240 V | topLED 7 W DC - 8 W AC | CRI 80
8406

Double emission wall lights for indoor application. The warm white LED light source with a diffused light distribution is composed of 40 topLED LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 1022 lm, with a 146.0 lm/W nominal luminous efficacy.

The device body is made of iron and features a polished (galvanic) chrome finish, processed by means of electroplating; the diffuser is made of PC; the mounting frame is made of iron, with a polished (galvanic) chrome finish, processed by means of electroplating.

The ingress protection degree is IP44; the total weight is of 0.545 kg.

The total absorbed power is 8 W

The device features protection class I and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	69 %
Lichtstrom (Lichtquelle)	1022 lm
Leuchten Lichtstrom	710 lm
Consumption	8 W
Leuchten Lichtausbeute	88 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	25°C

LED Life / Failure Ratio

L70 B10 C0 102000h (at Tj 115 Ta 25)

L90 B10 C0 55000h

UGR

UGR axial	17.3
UGR transversal	17.6
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C90/C270	180°
Optik C0/C180	115°
Light distribution simmetry	Symmetrical 2 assis

