
Maxi Tube IN&OUT

198-264 V AC /176-276 V DC
topLED 20 W DC - 22 W AC | CRI 80
84374C12





Technische Daten	
Typ	Oberfläche - Industriebeleuchtung
Installationsposition	Wand - Decke
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	topLED
Optik	120°
Light emission direction	frontal
Lampe Nennleistung	20 W DC
Gesamtleistung	22 W
Lichtstrom (Lichtquelle)	3032 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	198 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	6500 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP67
IK	IK08
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	DALI
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	1+1 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.8 Kg
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	Ja

Oberfläche Oberfläche Gehäuse	
Material	UV beständiges Polycarbonat
Farbe	Opal

Oberfläche Oberfläche diffusor	
Material	UV beständiges Polycarbonat
Farbe	Opal

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

198-264 V AC /176-276 V DC | topLED 20 W DC - 22 W AC | CRI 80
84374C12

Single emission lines for outdoor application. The cold white LED light source is composed of 84 topled LEDs with CCT of 6500 K and a CRI 80; the source luminous flux is 3032 lm, with a 151.6 lm/W nominal luminous efficacy.

The device body is made of uv resistant polycarbonate and features a opaline finish; the diffuser is made of uv resistant polycarbonate.

The ingress protection degree is IP67; the total weight is of 0.8 kg.

The total absorbed power is 22 W The power supply cable is included and features a 1+1 m length.

The device features protection class II and can be wall lights or ceiling-mounted.


Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält 3 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	96 %
Lichtstrom (Lichtquelle)	3032 lm
Leuchten Lichtstrom	2941 lm
Consumption	22 W
Leuchten Lichtausbeute	133 lm/W
Farbtemperatur	6500 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	35°C

LED Life / Failure Ratio
L70 B10 C0 145600h (at Tj 65 Ta 25)
L80 B10 C0 92440h (at Tj 65 Ta 25)
L90 B10 C0 45500h (at Tj 65 Ta 25)

OPTICAL	
Optik C90/C270	121°
Optik C0/C180	107°
Light distribution simmetry	Symmetrical 2 assis



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Maxi Tube IN&OUT | Industrial Lighting | Accessories
84374C12





Befestigungssatz

Code
99226





Befestigungssatz

Code
99227



Befestigungssatz

Code
98695



Stecker - DALI-Schnellverbinder IP68 Buchse / Stecker (5-polig)
Querschnitt 0.25-1.5 mm²; außendurchmesser: 7.0-13.5 mm.

Code
99768



Kabel
Typ Kabel power + signal cable; Länge 1000 mm; isolierung singolo/doppio con schermatura; querschnitt 1.5 mm²; farben: schwarz - blau - grau - braun.

Code
83205

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.