
Scheinwerfer | 56 x powerLEDs 450 W DC 3600 mA
CRI 70
84432C35







Technische Daten	
Typ	Oberfläche
Installationsposition	Wand - Decke - Boden
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	powerLEDs
Optik	Medium Wide Flood
Light emission direction	frontal
Lampe Nennleistung	450 W DC
Lichtstrom (Lichtquelle)	78781 lm
Eingangsspannungsbereich	3600mA
Ähnlichste Farbtemperatur / Tone	5700 K
Farbwiedergabeindex	70 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP66
IK	IK08
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Orientabile
Gesamtwinkel (vertikale Ebene)	90 °
Gesamtwinkel (horizontale Ebene)	0 °
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	1 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Oberfläche Seitenwind ausgesetzt	0,018 m²
Oberfläche dem Wind ausgesetzt - Plan	0,134 m²
Nettogewicht	9.5 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein
Technische Merkmale des Produkts	TCS

Oberfläche Oberfläche Gehäuse	
Material	Stranggepresstes Aluminium EN AB - 46100
Farbe	Aluminium

Oberfläche Oberfläche diffusor	
Material	Extra-helles Glas - Gehärtet
Farbe	Transparent

Oberfläche Oberfläche bügel	
Material	Verzinktes Eisen
Farbe	Text brilliant grey RAL 9006
Bearbeitungstyp	Kataphorese + Pulvermalerei

Elektronik



83030
DALI Controller (- art.)



83031
1-10V Controller (- art.)



83211
1-10V Controller (1 art.)



83212
1-10V - PWM Controller (1 art.)

Cables Electrification	
Cable connector	No

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Scheinwerfer | 56 x powerLEDs 450 W DC 3600 mA | CRI 70
84432C35

Single emission projectors for outdoor application. The cold white LED light source with a medium wide flood light distribution is composed of 56 powerled LEDs with CCT of 5700 K and a CRI 70; the source luminous flux is 78781 lm, with a 175.1 lm/W nominal luminous efficacy.


The device body is made of die-cast aluminium en ab - 46100 and features a aluminium finish; the diffuser is made of extra clear glass - tempered.


The ingress protection degree is IP66; the total weight is of 9.5 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 450 W The power supply cable is included and features a 1 m length.

The device features protection class III and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	67 %
Lichtstrom (Lichtquelle)	78781 lm
Leuchten Lichtstrom	53385 lm
Consumption	450 W
Leuchten Lichtausbeute	118 lm/W
Farbtemperatur	5700 K
Standard Deviation of Colour Matching	5 Step MacAdam
Farbwiedergabeindex	70 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L90 B10 C0 90000h (at Tj 65 Ta 25)

UGR	
UGR axial	25.5
UGR transversal	27.9
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	35°
Optik C0/C180	43°
Light distribution simmetry	Symmetrical 2 assis

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.