


220-240 V | 216 topLED 31 W DC - 36 W AC | CRI 90
8452



Technische Daten	
Designer	Mirco Crosatto
Jahr der Verwirklichung	2014
Typ	Stehleuchten
Installationsposition	Boden
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	frontal
Lampe Nennleistung	31 W DC
Gesamtleistung	36 W
Lichtstrom (Lichtquelle)	4640 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	220 - 240 V AC
Frequency	60 - 50 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	PUSH DIM
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Steckdose	Type F+E
Kabellänge	4.7 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	7.5 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Farbe	Text white RAL9003
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor	
Material	PC
Farbe	Weiß
Bearbeitungstyp	Satinieren

220-240 V | 216 topLED 31 W DC - 36 W AC | CRI 90
8452

Double emission floor lamp for indoor application. The warm white LED light source with a diffused light distribution is composed of 216 topLED LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 4640 lm, with a 149.7 lm/W nominal luminous efficacy.



The device body is made of aluminium and features a text white ral9003 finish, processed by means of coating; the diffuser is made of PC with a satin finishing treatment.

The ingress protection degree is IP20; the total weight is of 7.5 kg.

The total absorbed power is 36 W The power supply cable is included and features a 4.7 m length.

The device features protection class I and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse	
Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse E.	

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	51 %
Lichtstrom (Lichtquelle)	4640 lm
Leuchten Lichtstrom	2402 lm
Consumption	36 W
Leuchten Lichtausbeute	66 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	25°C

LED Life / Failure Ratio	
L70 B10 C0 102000h (at Tj 115 Ta 25)	
L90 B10 C0 55000h	

UGR	
UGR axial	14.6
UGR transversal	15.5
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	113°
Optik C0/C180	164°
Light distribution simmetry	Symmetrical 2 assis