Downlights | 1 x powerLED 1 W DC 350 mA
85014M12



15

Technische Daten	
Installationsposition	Wand - Decke
Installationsumgebung	Indoor
Isolierklasse	3
IP	IP44
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	0.12 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.015 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Messing gebürstet
Farbe	Brushed nickel
Bearbeitungstyp	Bürsten

Elektronik

89144
On/Off Driver 198~264V AC / 180~275V DC (1 - 2 art.)

89145
On/Off Driver 198~264V AC / 180~275V DC (1 art.)

99374
On/Off Driver 198~264V AC / 176~275V DC 75 W (- art.)

99708
1-10V - 0-10V Converter V DC (- art.)

99711
DALI Converter V DC (- art.)

99375
On/Off Driver 198~264V AC (8 - 12 art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Aspho_R | Downlights | Accessories
85014M12

Einbaugehäuse
installationsposition: wand; typ installation: mauerwerk L=35mm, H=20mm, D=20mm.
Material:Kunststoff ABS, farbe:Black.

Code
84335

Einbaugehäuse
installationsposition: decke; typ installation: mauerwerk L=48mm, H=60mm, D=60mm.
Material:Kunststoff ABS, farbe:Black.

Code
84916

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.