


Downlights | 1 x powerLED 2 W DC 630 mA | CRI 80
86883W00



Technische Daten	
Installationsposition	Wand - Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	powerLED
Optik	Diffuses
Lampe Nennleistung	2 W DC
Lichtstrom (Lichtquelle)	233 lm
Eingangsspannungsbereich	630mA
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP44
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	0.12 m
Harzbeschichtung	Ja
Einbautiefe	45 mm
Typ Lichtabstrahlung	Einflamig
Nettogewicht	0.07 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse

Material	Edelstahl 316
Farbe	Stahl
Bearbeitungstyp	Kugelstrahlen

Oberfläche Oberfläche strahler

Material	Aluminium
Farbe	Anodised aluminium
Bearbeitungstyp	Eloxierung

Elektronik



89147
On/Off Driver 198-264V AC / 180-275V DC (1 - 2 art.)



99105
On/Off Driver 198-264V AC (1 - 12 art.)



99374
On/Off Driver 198-264V AC / 176-275V DC 75 W (1 - 37 art.)



99710
1-10V - 0-10V Converter V DC (1 art.)



99713
DALI Converter V DC (1 art.)



99376
On/Off Driver 198-264V AC (1 - 6 art.)

Downlights | 1 x powerLED 2 W DC 630 mA | CRI 80
86883W00

Single emission recessed downlights for indoor application. The warm white LED light source with a diffused light distribution is composed of 1 powered LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 233 lm, with a 116.5 lm/W nominal luminous efficacy.


The device body is made of stainless steel and features a steel finish, processed by means of shot peening. The robust steel structure enhances the fixture's design and ensures long-lasting performance, even in the most demanding environments.

The ingress protection degree is IP44; the total weight is of 0.07 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 2 W The power supply cable is included and features a 0.12 m length.

The device features protection class III and can be wall lights or ceiling-mounted, with a 29 mm diameter hole (in plasterboard) with an outer casing, code 84901(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	1.60 1.62	E(0°) 229 E(C90) 17 E(C0) 17
1.0	3.20 3.24	E(0°) 57 E(C90) 4 E(C0) 4
1.5	4.80 4.86	E(0°) 25 E(C90) 2 E(C0) 2
2.0	6.40 6.48	E(0°) 14 E(C90) 1 E(C0) 1
2.5	8.00 8.10	E(0°) 9 E(C90) 1 E(C0) 1
3.0	9.60 9.71	E(0°) 6 E(C90) 0 E(C0) 0

— C0/C180 (Half-peak divergence: 116.6°)
— C90/C270 (Half-peak divergence: 116.0°)

Energieeffizienzklasse

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	75 %
Lichtstrom (Lichtquelle)	233 lm
Leuchten Lichtstrom	177 lm
Consumption	2,0 W
Leuchten Lichtausbeute	88 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	1.5 Step
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 1240219h (at Tj 65 Ta 25)

L80 B10 C0 745627h (at Tj 65 Ta 25)

L90 B10 C0 309367h (at Tj 65 Ta 25)


UGR

UGR axial	37.2
UGR transversal	36.8
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C0/C180	116°
Light distribution simmetry	Symmetrical

Nitum_R | Downlights | Accessories
86883W00



Einbaugehäuse
installationsposition: decke; typ installation: mauerwerk L=69mm, H=60mm, D=60mm.
Material:Kunststoff ABS, farbe:Black.

Code
84901