


Pendelleuchte | 220-240 V
8 topLED 32 W DC - 36 W AC | CRI 90
8845



Technische Daten	
Typ	Oberfläche
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward and upward
Lampe Nennleistung	32 W DC
Gesamtleistung	36 W
Lichtstrom (Lichtquelle)	4828 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	220 - 240 V AC
Frequency	60 - 50 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	DALI - PUSH DIM
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	2.8 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	2.15 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse

Material	Aluminium
Farbe	Text white RAL9003
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor

Material	PMMA
Farbe	Opal

Oberfläche Oberfläche fassung

Material	Eisen
Farbe	Text white RAL9003
Bearbeitungstyp	Lackierung

Cables Electrification+suspension

Max. Kabellänge	2800 mm
-----------------	---------

Pendelleuchte | 220-240 V | 8 topLED 32 W DC - 36 W AC | CRI 90
8845

Double emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 256 topLED LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 4828 lm, with a 150.9 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a text white ral9003 finish, processed by means of coating; the diffuser is made of pmma; the mounting frame is made of iron, with a text white ral9003 finish, processed by means of coating.

The ingress protection degree is IP20; the total weight is of 2.15 kg.

The total absorbed power is 36 W The power supply cable is included and features a 2.8 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse

Dieses Produkt enthält 8 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	86 %
Lichtstrom (Lichtquelle)	4828 lm
Leuchten Lichtstrom	4199 lm
Consumption	36 W
Leuchten Lichtausbeute	116 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	25°C

LED Life / Failure Ratio

L70 B10 C0 102000h (at Tj 115 Ta 25)


L90 B10 C0 55000h

UGR

UGR axial	21.6
UGR transversal	18
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C90/C270	180°
Optik C0/C180	124°
Light distribution simmetry	Symmetrical 2 assis



Tu-O | Pendant Luminaires | Accessories
8845



Blendschutz

Material:Eisen, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.

Code

KIT0112