


Uplights | 1 x powerLED 1 W DC 350 mA | CRI 80
92092N00



Technische Daten	
Typ	Frame
Installationsposition	Boden
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	powerLED
Optik	Diffuses
Light emission direction	upward
Lampe Nennleistung	1 W DC
Lichtstrom (Lichtquelle)	165 lm
Eingangsspannungsbereich	350mA
Ähnlichste Farbtemperatur / Tone	4000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP66
IK	IK05
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	Ja
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Ja
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	1 m
Harzbeschichtung	Ja
Einbautiefe	28 mm
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.066 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse

Material	Messing gebürstet
Farbe	Text brilliant grey RAL 9006
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor

Material	Extra-helles Glas - Gehärtet
Farbe	Transparent

Elektronik



89421
On/Off Driver 198-264V AC / 176-275V DC



89419
On/Off Driver 198-264V AC / 176-275V DC



C-E200004
Push and Simply Dim - DALI-2 Controller



C-E200006
On/Off Driver 198-264V AC / V DC

Cables Electrification

Cable connector	No connector - Neoprene 2x0.5mm²
-----------------	----------------------------------

Uplights | 1 x powerLED 1 W DC 350 mA | CRI 80
92092N00

Single emission uplights for outdoor application. The natural white LED light source with a diffused light distribution is composed of 1 powered LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 165 lm, with a 165.0 lm/W nominal luminous efficacy.


The device body is made of brass and features a text brilliant grey ral 9006 finish, processed by means of coating; the diffuser is made of extra clear glass - tempered.

The ingress protection degree is IP66; the total weight is of 0.066 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 1 W The power supply cable is included and features a 1 m length.

The device features protection class III and can be floor-mounted, with a 29 mm diameter hole (in plasterboard) with an outer casing, code 84915(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	1.28	46
1.0	2.55	11
1.5	3.83	5
2.0	5.10	3
2.5	6.38	2
3.0	7.65	1

Legend: C0/C180 (Half-peak divergence: 104.2°), C90/C270 (Half-peak divergence: 103.8°)

Energieeffizienzklasse

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	19 %
Lichtstrom (Lichtquelle)	165 lm
Leuchten Lichtstrom	32 lm
Consumption	1,0 W
Leuchten Lichtausbeute	32 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	1.5 Step
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 1240219h (at Tj 65 Ta 25)

L80 B10 C0 745627h (at Tj 65 Ta 25)

L90 B10 C0 309367h (at Tj 65 Ta 25)

UGR

UGR axial	29.1
UGR transversal	29
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C0/C180	104°
Light distribution simmetry	Symmetrical

Beret_Q | Uplights | Accessories
92092N00

		<p>Einbaugehäuse</p> <p>installationsposition: wand; typ installation: mauerwerk L=49mm, H=60mm, D=60mm.</p> <p>Material:Kunststoff ABS, farbe:Black.</p>	<p>Code</p> <p><u>84915</u></p>
		<p>Einbaugehäuse</p> <p>installationsposition: decke; typ installation: mauerwerk L=42mm, H=35mm, D=35mm.</p> <p>Material:Kunststoff ABS, farbe:Black.</p>	<p>Code</p> <p><u>84336</u></p>