

Wandleuchten | 1 x powerLED 2 W DC 630 mA | Rot
92562R05



52



Technische Daten	
Installationsposition	Wand - Decke
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	powerLED
Optik	Ultra Spot
Lampe Nennleistung	2 W DC
Eingangsspannungsbereich	630mA
Ähnlichste Farbtemperatur / Tone	Rot
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP65
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	1 m
Harzbeschichtung	Ja
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.150 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Edelstahl --
Farbe	Stahl
Bearbeitungstyp	Bürsten

Elektronik



89168
Multi Power V AC (- art.)



89160
On/Off Driver 190~250V AC / 260~360V DC (- art.)



89420
On/Off Driver 198~264V AC / 176~275V DC (- art.)

Wandleuchten | 1 x powerLED 2 W DC 630 mA | Rot
92562R05

Single emission wall lights for outdoor application. The red LED light source with a ultra spot light distribution is composed of 1 powered LEDs.

The device body is made of stainless steel and features a steel finish, processed by means of brushing. The robust steel structure enhances the fixture's design and ensures long-lasting performance, even in the most demanding environments.

The ingress protection degree is IP65; the total weight is of 0.150 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 2 W The power supply cable is included and features a 1 m length.

The device features protection class III and can be wall lights or ceiling-mounted, with a 52 mm diameter hole (in plasterboard) with an outer casing, code 84338(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Typische Temperatur am Glas	40°C
LED Life / Failure Ratio	
L70 B10 C0 247450h	

Cut | Wall Lights | Accessories
92562R05



Einbaugehäuse
installationsposition: wand; typ installation: mauerwerk L=72mm, H=62mm, D=62mm.
Material:Kunststoff ABS, farbe:Black.

Code
84338