


Wandleuchten | 220-240 V
topLED 19 W DC - 21 W AC | CRI 80
9340



Technische Daten	
Jahr der Verwirklichung	2020
Typ	Wandleuchten
Installationsposition	Wand
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	19 W DC
Gesamtleistung	21 W
Lichtstrom (Lichtquelle)	2952 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	220 - 240 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP65
IK	IK10
Glühdrahtprüfung	960°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Ja
Typ Lichtabstrahlung	Einflammmig
Nettogewicht	1.940 Kg
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	Ja

Oberfläche Oberfläche Gehäuse

Material	Edelstahl --
Farbe	Dark brown
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor

Material	PU
Farbe	Opal

Oberfläche Oberfläche fassung

Material	Edelstahl --
Farbe	Dark brown
Bearbeitungstyp	Lackierung

Wandleuchten | 220-240 V | topLED 19 W DC - 21 W AC | CRI 80
9340

Single emission wall lights for outdoor application. The warm white LED light source with a diffused light distribution is composed of 126 topLED LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 2952 lm, with a 155.4 lm/W nominal luminous efficacy.

The device body is made of stainless steel and features a dark brown finish, processed by means of coating; the diffuser is made of pu; the mounting frame is made of stainless steel, with a dark brown finish, processed by means of coating. The robust steel structure enhances the fixture's design and ensures long-lasting performance, even in the most demanding environments.

The ingress protection degree is IP65; the total weight is of 1.940 kg.

The total absorbed power is 21 W

The device features protection class II and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse

Dieses Produkt enthält 3 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	33 %
Lichtstrom (Lichtquelle)	2952 lm
Leuchten Lichtstrom	1001 lm
Consumption	21 W
Leuchten Lichtausbeute	47 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio

L70 B10 C0 191000h (at Tj 115 Ta 25)

L80 B10 C0 120000h

L90 B10 C0 58000h

UGR

UGR axial	17.5
UGR transversal	25.8
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C90/C270	82°
Optik C0/C180	123°
Light distribution simmetry	Symmetrical 2 assis

