Uplights | topLED 1.44 W DC 24 V | CRI 80

96661W00



Technische Daten	
Typ	Frameless
Installationsposition	Wand - Boden
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Lampe Nennleistung	1.44 W DC
Lichtstrom (Lichtquelle)	60 lm
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP67
IK	IK09
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Ja
Überrollbarkeit	2000 Kg
Einschließlich Kabel	Ja
Kabellänge	1.5 m
Harzbeschichtung	Ja
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.210 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Farbe	Text brilliant grey RAL 9006
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor	
Material	PC
Farbe	Transparent
Bearbeitungstyp	Sandstrahlen

Elektronik

89488
On/Off Driver 190~250V AC / 180~275V DC 14.4 W (1 - 10 art.)

89179
On/Off Driver 198~264V AC 24 W (1 - 16 art.)

89359
On/Off Driver 198~264V AC / V DC (1 - 33 art.)

99332
1-10V Controller (1 - 104 art.)

99722
DALI Controller 90~305V AC / V DC (- art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Uplights | topLED 1.44 W DC 24 V | CRI 80
96661W00

Single emission uplights for outdoor application. The warm white LED light source with a diffused light distribution is composed of 4 topled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 60 lm, with a 41.7 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a text brilliant grey ral 9006 finish, processed by means of coating; the diffuser is made of PC with a sandblasting treatment.

The ingress protection degree is IP67; the total weight is of 0.210 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 1.44 W The power supply cable is included and features a 1.5 m length.

The device features protection class III and can be wall lights or floor-mounted with an outer casing, code 98402(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	100 %
Lichtstrom (Lichtquelle)	60 lm
Leuchten Lichtstrom	60 lm
Consumption	1,4 W
Leuchten Lichtausbeute	60 lm/W
Farbtemperatur	3000 K
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

OPTICAL	
Optik C0/C180	180°
Light distribution simmetry	Symmetrical



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Concentrica_Q | Uplights | Accessories
96661W00

Einbaugehäuse
L=52mm, H=102mm, D=52mm.
Material:Stahl AISI 304, farbe:Stahl.

Code
98402

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.