Paseo_X DALI

85-277 V | 12 x powerLED 7 W DC - 7.7 W AC
CRI 80
97256M25



Technische Daten	
Typ	Frameless
Installationsposition	Wand - Decke - Boden
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	powerLED
Optik	Elliptical
Light emission direction	frontal
Lampe Nennleistung	7 W DC
Gesamtleistung	7.7 W
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	85 - 277 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	2700 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP67
IK	IK08
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Control unit/Driver
Leuchte dimmbar	DALI
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Ja
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	0.25 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.39 Kg
Schutz vor elektrostatischen Entladungen	4 KV
Schutz vor Stoßspannungen	6 KV
Technische Merkmale des Produkts	TCS - UV Resistant

Oberfläche Oberfläche Gehäuse	
Material	UV beständiges Polycarbonat
Farbe	Transparent

Oberfläche Oberfläche diffusor	
Material	UV beständiges Polycarbonat
Farbe	Transparent

Cables Electrification	
Cable connector	Female Socket 4 Pin M12
IP (locked condition)	67
Cable connector	Male Plug 4 pin M12
IP (locked condition)	67

Cables Signal	
Cable connector	Female Socket 5 Pin M12
IP (locked condition)	67
Cable connector	Male Plug 5 Pin M12
IP (locked condition)	67

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

85-277 V | 12 x powerLED 7 W DC - 7.7 W AC | CRI 80
97256M25

Single emission lines for outdoor application. The super warm white LED light source with a elliptical light distribution is composed of 12 powerled LEDs with CCT of 2700 K and a CRI 80.

Product suitable for installations in coastal areas with high salinity and strong exposure to atmospheric agents.

The device body is made of uv resistant polycarbonate and features a transparent finish; the diffuser is made of uv resistant polycarbonate.

The ingress protection degree is IP67; the total weight is of 0.39 kg.

The total absorbed power is 7 W The power supply cable is included and features a 0.25 m length.

The device features protection class II and can be wall lights, ceiling or floor-mounted with an outer casing, code 98843(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält 12 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Leuchten Lichtstrom	703 lm
Consumption	7.7 W
Leuchten Lichtausbeute	91 lm/W
Farbtemperatur	2700 K
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 1240219h (at Tj 65 Ta 25)
L80 B10 C0 745627h (at Tj 65 Ta 25)
L90 B10 C0 309367h (at Tj 65 Ta 25)

UGR	
UGR axial	16.2
UGR transversal	22.1
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	28°
Optik C0/C180	48°
Light distribution simmetry	Symmetrical 2 assis





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Paseo_X DALI | Lines | Accessories
97256M25

Kabel und Stecker - DMX
Länge 5000 mm; isolierung doppio; kabelklemme: nein; außendurchmesser: 4.5 mm.

Code
89189

Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 5m)
Länge 5000 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun.

Code
89190

Kabel und Stecker - DMX - Conn. M.5 pin M12 + M.3 pin XLR (L 5m)
Länge 5000 mm; isolierung doppio; kabelklemme: nein.

Code
89186

Kabel und Stecker
Länge 10000 mm; isolierung doppio; kabelklemme: nein.

Code
89187

Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 5m)
Länge 5000 mm; isolierung doppio; kabelklemme: nein.

Code
98149

Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 10m)
Länge 10000 mm; isolierung doppio; kabelklemme: nein.

Code
89188

Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 1,5m)
Länge 1500 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun.

Code
99216

Kabel und Stecker - Verlängerungskabel
Länge 1000 mm; isolierung doppio; kabelklemme: nein.

Code
98437

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Paseo_X DALI | Lines | Accessories
97256M25

Kabel und Stecker - DMX - Conn. M.5 pin M12 + M.5 pin XLR (L 5m)
Länge 5000 mm; isolierung doppio; querschnitt 0.25 mm²; kabelklemme: nein.

Code
98493

Kabel und Stecker - DMX - Conn. M.5 pin M12 + F.3 pin XLR (L 5m)
Länge 5000 mm; isolierung doppio; kabelklemme: nein.

Code
98494

Endkappe - zwei Profil Endkappen

Code
98553



Endkappe

Code
98554

Endkappe

Code
98466



Endkappe

Code
98465

Endkappe

Code
98464

Endkappe
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98876

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Paseo_X DALI | Lines | Accessories
97256M25



Endkappe
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98840



Endkappe
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98841



Schlüssel - Paseo Ausziehschlüssel
Material:Edelstahl --, farbe:Stahl.

Code
98475



Einbaugehäuse
installationsposition: boden; typ installation: mauerwerk L=576mm, H=49mm, D=36mm.
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98430



Einbaugehäuse
installationsposition: boden; typ installation: mauerwerk L=577mm, H=49mm, D=28mm.
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98468



Einbaugehäuse
installationsposition: boden; typ installation: mauerwerk L=577mm, H=29.8mm, D=28mm.
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98472



Einbaugehäuse
installationsposition: decke; typ installation: gipskarton L=577mm, H=55.5mm, D=36mm.
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98435



Einbaugehäuse
installationsposition: decke; typ installation: gipskarton L=577mm, H=89mm, D=69.5mm.
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98434

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Paseo_X DALI | Lines | Accessories
97256M25



Einbaugehäuse
installationsposition: wand; typ installation: mauerwerk L=577mm, H=66mm, D=32mm.
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98839



Einbaugehäuse
installationsposition: wand; typ installation: mauerwerk L=581mm, H=91mm, D=64.5mm.
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
98843

Befestigungssatz
Material:UV beständiges Polycarbonat, farbe:Transparent.

Code
98771



Befestigungsplatte - Befestigungsbasis
Material:Stahl AISI 304, farbe:Stahl.

Code
98772

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.