



Unterwasserleuchten - LED Strip | 112 topLED 6 W DC 24 V | 9.54 W/m | 1151.03 Lm/m |

CRI >90

**C0012TDI00629**

Single emission submerged or led strip for outdoor application. The brilliant white LED light source with a diffused light distribution is composed of 112 topLEDs with CCT of 3500 K and a CRI >90; the source luminous flux is 724 lm, with a 120.7 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish; the diffuser is made of pu.

The ingress protection degree is IP68; the total weight is of 0.06 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 6 W The power supply cable is included and features a 10 m length.

The device features protection class III and can be wall lights or ceiling-mounted with an outer casing, code C-C300001(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

## Energieeffizienzklasse

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E.

## Illuminotechnical Eigenschaften

|                                       |                |
|---------------------------------------|----------------|
| Lichtstrom (Lichtquelle)              | 724 lm         |
| Farbtemperatur                        | 3500 K         |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Farbwiedergabeindex                   | >90 Ra         |
| Standardumgebungstemperatur           | -20 / +55°C    |

## LED Life / Failure Ratio

L70 B10 C0 191000h

L80 B10 C0 120000h

L90 B10 C0 58000h

Rubber 3D PROtection | LED Strip | Accessories  
C0012TDI00629




Profil - Lineares Weiss Pvc-Profil 19x18x1000mm für Rubber 3D PROtection  
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

**Code**  
C-K100002




Profil - Lineares Weiss Pvc-Profil 19x18x2000mm für Rubber 3D PROtection  
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

**Code**  
C-K100001



Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x2000mm für Rubber 3D PROtection  
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

**Code**  
C-K100004



Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x1000mm für Rubber 3D PROtection  
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

**Code**  
C-K100005



Clip - Weißes pvc lineares Profil 19x18x50mm für Rubber 3D PROtection  
installationsposition: wand, decke

**Code**  
C-K100003




Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x50mm für Rubber 3D PROtection  
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

**Code**  
C-K100006



Einbaugehäuse - Gegengehäuse + Kabelverschraubung Betonbecken  
L=300mm, H=36mm, D=36mm.  
Material:Kunststoff ABS, farbe:Black.


**Code**  
C-C300001



Lochschablone  
Material:Aluminium, farbe:Polished aluminium.


**Code**  
C-V200005

Rubber 3D PROtection | LED Strip | Accessories  
C0012TDI00629




Lochschablone - Rubber Vorbereitungsset - Polystyrolstreifen

Code  
99521




Zubehör für Außengehäuse

Code  
C-K400165



Lochschablone - Rubber Vorbereitungsset - Polystyrolstreifen

Code  
C-K400170



Zubehör für Außengehäuse

Code  
C-K400171



Kabelklemme

Code  
98990



Stecker

Code  
89548



Kabelklemme  
Material:Kunststoff ABS, farbe:Black.

Code  
C-W300001



Strip Service - Doppelseitiges Klebeband 33 Meter

Code  
99520

Rubber 3D PROtection | LED Strip | Accessories

**C0012TDI00629**

---