

Unterwasserleuchten - LED Strip | 448 topLED 21.6 W DC 24 V | 14.98 W/m | CRI >90 |
RGBW - 3000
C0012VDI01442

Single emission submerged or led strip for outdoor application. The RGBW - 3000 K LED light source with a diffused light distribution is composed of 448 topLEDs with CCT of RGB-W 3000 K and a CRI >90; the source luminous flux is 765 lm, with a 35.4 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish; the diffuser is made of pu.

The ingress protection degree is IP68; the total weight is of 0.39 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 21.6 W The power supply cable is included and features a 10 m length.

The device features protection class III and can be wall lights or ceiling-mounted with an outer casing, code C-C300001(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse G.



Illuminotechnical Eigenschaften

Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	>90 Ra
Standardumgebungstemperatur	-20 / +55°C


LED Life / Failure Ratio

L90 B10 C0 54000h

Rubber 3D PROtection RGBW | LED Strip | Accessories
C0012VDI01442

		Profil - Lineares Weiss Pvc-Profil 19x18x1000mm für Rubber 3D PROtection Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.	Code <u>C-K100002</u>
		Profil - Lineares Weiss Pvc-Profil 19x18x2000mm für Rubber 3D PROtection Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.	Code <u>C-K100001</u>
		Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x2000mm für Rubber 3D PROtection Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.	Code <u>C-K100004</u>
		Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x1000mm für Rubber 3D PROtection Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.	Code <u>C-K100005</u>
		Clip - Weißes pvc lineares Profil 19x18x50mm für Rubber 3D PROtection installationsposition: wand, decke	Code <u>C-K100003</u>
		Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x50mm für Rubber 3D PROtection Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.	Code <u>C-K100006</u>
		Einbaugehäuse - Gegengehäuse + Kabelverschraubung Betonbecken L=300mm, H=36mm, D=36mm. Material:Kunststoff ABS, farbe:Black.	Code <u>C-C300001</u>
		Lochschablone Material:Aluminium, farbe:Polished aluminium.	Code <u>C-V200005</u>


Rubber 3D PROtection RGBW | LED Strip | Accessories
C0012VDI01442



Lochschablone - Rubber Vorbereitungsset - Polystyrolstreifen

Code


99521



Zubehör für Außengehäuse

Code


C-K400165



Lochschablone - Rubber Vorbereitungsset - Polystyrolstreifen

Code

C-K400170



Zubehör für Außengehäuse

Code

C-K400171



Kabelklemme

Material:Kunststoff ABS, farbe:Black.

Code

C-W300001



Strip Service - Doppelseitiges Klebeband 33 Meter

Code

99520