


Downlights | 3 x powerLEDs 6 W DC 630 mA | CRI 90
C00150WBWMW



Technische Daten	
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	powerLEDs
Optik	Medium Wide Flood
Light emission direction	downward
Lampe Nennleistung	6 W DC
Lichtstrom (Lichtquelle)	639 lm
Eingangsspannungsbereich	630mA
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	Ja
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	0.170 m
Harzbeschichtung	Nein
Einbautiefe	67 mm
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.215 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein
Technische Merkmale des Produkts	TVS

Oberfläche Oberfläche Gehäuse

Farbe	Weiß + Schwarz
Bearbeitungstyp	Pulverbeschichtung mit duroplastischen Pulvern

Oberfläche Oberfläche diffusor

Material	Pom-C
Farbe	Schwarz

Oberfläche Oberfläche strahler

Material	Aluminiumlegierung 6060
Farbe	Anodised black aluminium
Bearbeitungstyp	Anodisierung 15 µm

Elektronik

	99115 1-10V - N/O button Multi Power 198-264V AC / V DC (1 - 3 art.)
---	---

	99105 On/Off Driver 198-264V AC (2 - 4 art.)
---	---

	99376 On/Off Driver 198-264V AC (1 - 2 art.)
---	---

	C-E100001 Push and Simply Dim - DALI-2 Multi Power 198-264V AC / V DC (2 - 4 art.)
---	---

Cables Electrification

Cable connector	No
-----------------	----

Downlights | 3 x powerLEDs 6 W DC 630 mA | CRI 90
C00150WBWMW

Single emission recessed downlights for indoor application. The warm white LED light source is composed of 3 powered LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 639 lm, with a 106.5 lm/W nominal luminous efficacy.



The device body and features a white + black finish, processed by means of powder coating with thermosetting powders; the diffuser is made of pom-c.

The ingress protection degree is IP20; the total weight is of 0.215 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 6 W The power supply cable is included and features a 0.170 m length.

The device features protection class III and can be ceiling-mounted, with a 113 x 42 mm hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	54 %
Lichtstrom (Lichtquelle)	639 lm
Leuchten Lichtstrom	347 lm
Consumption	6 W
Leuchten Lichtausbeute	57 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 214455h (at Tj 65 Ta 25)

L80 B10 C0 136355h (at Tj 65 Ta 25)

L90 B10 C0 67466h (at Tj 65 Ta 25)

UGR

UGR transversal	10.8
UGR axial	9.6
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C0/C180	49°
Light distribution simmetry	Symmetrical