
Scheinwerfer | 176-264 V AC /176-280 V DC
1 arrayLED 24 W DC - 27 W AC | CRI 98
C00449BBWWF







Technische Daten	
Typ	Schiene
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	arrayLED
Optik	Wide Flood
Light emission direction	frontal
Lampe Nennleistung	24 W DC
Gesamtleistung	27 W
Lichtstrom (Lichtquelle)	3749 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	176 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	98 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	DALI-2 - PUSH DIM
Schwenkbarkeit	Orientabile
Gesamtwinkel (vertikale Ebene)	90 °
Gesamtwinkel (horizontale Ebene)	360 °
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.66 Kg
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	2 KV

Oberfläche Oberfläche Gehäuse	
Material	Stranggepresstes Aluminium EN AB - 46100
Farbe	Text black RAL9005
Bearbeitungstyp	Pulverbeschichtung mit duroplastischen Pulvern

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Scheinwerfer | 176-264 V AC /176-280 V DC | 1 arrayLED 24 W DC - 27 W AC | CRI 98
C00449BBWWF

Single emission projectors for indoor application. The warm white LED light source is composed of 1 arrayled LEDs with CCT of 3000 K and a CRI 98; the source luminous flux is 3749 lm, with a 156.2 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a text black ral9005 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP20; the total weight is of 0.66 kg.

The total absorbed power is 27 W

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.


Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E.


Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	75 %
Lichtstrom (Lichtquelle)	3749 lm
Leuchten Lichtstrom	2845 lm
Consumption	27 W
Leuchten Lichtausbeute	105 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Farbwiedergabeindex	98 Ra
Black Body Locus	Below
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C


LED Life / Failure Ratio
L70 B10 C0 235315h (at Tj 65 Ta 25)
L80 B10 C0 147343h (at Tj 65 Ta 25)
L90 B10 C0 69745h (at Tj 65 Ta 25)


UGR	
UGR axial	22.4
UGR transversal	22.4
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	49°
Light distribution simmetry	Symmetrical









Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Optus_T V2 | Projectors | Accessories
C00449BBWWF



Optik - WIDE FLOOD
Lichtverteilung: medium flood,Material Verkleidung: uv beständiges polycarbonat

Code
C-U300017



Optik - FLOOD
Lichtverteilung: flood,Material Verkleidung: uv beständiges polycarbonat

Code
C-U300016



Optik - SPOT
Lichtverteilung: spot,Material Verkleidung: uv beständiges polycarbonat

Code
C-U300015



Blendschutz
Blendschutzart: wabenraster.
Material:Pom-C, farbe:Schwarz.


Code
C-U300014



Diffusor - Es ist nicht mit 60°-Optiken kompatibel


Code
C-U300013






Code
81095





Code
81094






Endkappe
Material:Schwarz, farbe:Black.

Code
81085

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Optus_T V2 | Projectors | Accessories
C00449BBWWF





Endkappe
Material:Weiß.

Code
81084





Drahtabdeckung
Material:Schwarz, farbe:Black.

Code
83250

Drahtabdeckung
Material:Weiß.


Code
83249






Drahtabdeckung
Material:PC, farbe:Black.


Code
81079





Drahtabdeckung
Material:PC, farbe:Weiß.

Code
81078





Drahtabdeckung
Material:PC, farbe:Black.

Code
81073





Drahtabdeckung
Material:PC, farbe:Weiß.

Code
81072






Klammer
L=180mm, H=24mm, D=20mm.
Material:Aluminium, farbe:Schwarz RAL 9005, bearbeitungstyp :Lackierung.

Code
81026

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Optus_T V2 | Projectors | Accessories
C00449BBWWF






Klammer
L=180mm, H=24mm, D=20mm.
Material:Aluminium, farbe:Weiß RAL 9010, bearbeitungstyp :Lackierung.

Code
81025





Klammer
L=180mm, H=24mm, D=26mm.
Material:Aluminium, farbe:Anodised aluminium, bearbeitungstyp :Eloxierung.

Code
81024



Hängeleuchten
Material:Kunststoff, farbe:Black.


Code
81019



Hängeleuchten
Material:Kunststoff, farbe:Weiß.

Code
81018





Hängeleuchten
Material:Kunststoff, farbe:Black.


Code
81009



Hängeleuchten
Material:Kunststoff, farbe:Weiß.

Code
81007





Hängeleuchten
Material:Kunststoff, farbe:Black.

Code
81008



Hängeleuchten
Material:Kunststoff, farbe:Weiß.

Code
81006

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.


Optus_T V2 | Projectors | Accessories
C00449BBWWF



Werkzeug - Schneidezange S?9000/T
Material:Gummi, farbe:Black.


Code
81005





Code
81093






Code
81091





Drahtabdeckung
Material:PC, farbe:Black.


Code
81082






Drahtabdeckung
Material:PC, farbe:Weiß.


Code
81081






Drahtabdeckung
Material:PC, farbe:Black.


Code
81076





Drahtabdeckung
Material:PC, farbe:Weiß.

Code
81075





Drahtabdeckung
Material:PC, farbe:Black.

Code
81070

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Optus_T V2 | Projectors | Accessories
C00449BBWWF





Drahtabdeckung
Material:PC, farbe:Weiß.

Code
81069





Klammer
L=35mm, H=14mm, D=24mm.
Material:Aluminium, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.

Code
81088





Klammer
L=35mm, H=14mm, D=24mm.
Material:Aluminium, farbe:Weiß, bearbeitungstyp :Lackierung.

Code
81087





Klammer
L=35mm, H=14mm, D=24mm.
Material:Aluminium, farbe:Polished aluminium.

Code
81086



Hängeleuchten
Material:Kunststoff, farbe:Black.

Code
81022



Hängeleuchten
Material:Kunststoff, farbe:Weiß.


Code
81021



Deckenrosette - Schwarzes Aufhängungsset 5 m + Halterung (9000-KIT5-5-B)
Einschließlich Driver: Nein.
Material:Kunststoff, farbe:Black.

Code
81015






Deckenrosette - Weißes Aufhängungsset 5 m + Halterung (9000-KIT5-5-W)
Einschließlich Driver: Nein.
Material:Kunststoff, farbe:Weiß.

Code
81013

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Optus_T V2 | Projectors | Accessories
C00449BBWWF





Deckenrosette - Schwarzes Aufhängungsset 1,5 m + Halterung (9000-KIT5-1,5-B)
Einschließlich Driver: Nein.
Material:Kunststoff, farbe:Black.


Code
81014



Deckenrosette - Weißes Aufhängungsset 1,5 m + Halterung (9000-KIT5-1,5-W)
Einschließlich Driver: Nein.
Material:Kunststoff, farbe:Weiß.

Code
81012





Endkappe
Material:PC, farbe:Black.


Code
81003



Endkappe
Material:PC, farbe:Weiß.

Code
81002






Kabelverbindung
Typ linear.
Material:PC, farbe:Black.

Code
81061






Kabelverbindung
Typ linear.
Material:PC, farbe:Weiß.

Code
81060






Kabelverbindung
Typ linear.
Material:PC, farbe:Black.

Code
81058







Kabelverbindung
Typ linear.
Material:PC, farbe:Weiß.

Code
81057

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.


Optus_T V2 | Projectors | Accessories
C00449BBWWF






Kabelverbindung
Typ linear.
Material:PC, farbe:Black.

Code
81064






Kabelverbindung
Typ linear.
Material:PC, farbe:Weiß.

Code
81063






Kabelverbindung
Typ linear.
Material:PC, farbe:Black.

Code
81049






Kabelverbindung
Typ linear.
Material:PC, farbe:Weiß.

Code
81048






Kabelverbindung
Typ linear.
Material:PC, farbe:Black.

Code
81046






Kabelverbindung
Typ linear.
Material:PC, farbe:Weiß.


Code
81045






Kabelverbindung
Typ linear.
Material:PC, farbe:Black.

Code
81040





Kabelverbindung
Typ linear.
Material:PC, farbe:Weiß.

Code
81039

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Optus_T V2 | Projectors | Accessories
C00449BBWWF



Endkappe
Material:PC, farbe:Black.


Code
81000



Endkappe
Material:PC, farbe:Weiß.

Code
80999






Kabelverbindung
Typ linear.
Material:PC, farbe:Black.

Code
81055






Kabelverbindung
Typ linear.
Material:PC, farbe:Weiß.

Code
81054






Kabelverbindung
Typ linear.
Material:PC, farbe:Black.

Code
81052





Kabelverbindung
Typ linear.
Material:PC, farbe:Weiß.

Code
81051





Kabelverbindung
Typ flexible curve.
Material:PC, farbe:Black.

Code
81067





Kabelverbindung
Typ flexible curve.
Material:PC, farbe:Weiß.

Code
81066

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Optus_T V2 | Projectors | Accessories
C00449BBWWF





Kabelverbindung
Typ linear.
Material:PC, farbe:Black.

Code
81043






Kabelverbindung
Typ linear.
Material:PC, farbe:Weiß.

Code
81042






Stromversorgung
Material:PC, farbe:Black.

Code
81037






Stromversorgung
Material:PC, farbe:Weiß.

Code
81036






Stromversorgung
Material:PC, farbe:Black.

Code
81034






Stromversorgung
Material:PC, farbe:Weiß.

Code
81033






Schiene
Länge: 3000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.

Code
80995






Schiene
Länge: 2000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.

Code
80994

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Optus_T V2 | Projectors | Accessories
C00449BBWWF






Schiene
Länge: 1000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.

Code
80993






Schiene
Länge: 3000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
80992






Schiene
Länge: 2000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.


Code
80991






Schiene
Länge: 1000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.


Code
80990






Schiene
Länge: 3000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.


Code
83341






Schiene
Länge: 2000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.

Code
83340






Schiene
Länge: 1000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.

Code
83339






Schiene
Länge: 3000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83338

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Optus_T V2 | Projectors | Accessories
C00449BBWWF






Schiene
Länge: 2000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83337





Schiene
Länge: 1000mm; Typ Schiene: Standard.
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83336




Blendschutz
Blendschutzart: schermo cilindrico.
Material:Pom-C, farbe:Schwarz.

Code
C-U300029



Blendschutz
Blendschutzart: schermo cilindrico 45°.
Material:Pom-C, farbe:Schwarz.

Code
C-U300030



Blendschutz
Blendschutzart: frangiluce a croce.
Material:Pom-C, farbe:Schwarz.

Code
C-U300031

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.