Vissa_Q

Uplights - Step-Leuchten
2 x powerLED 0.7 W DC 220 mA | CRI 90
C00478NKWXF



Technische Daten	
Typ	Begehbar - Step-Leuchten
Installationsposition	Wand - Boden
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	powerLED
Optik	Extra Wide Flood
Light emission direction	upward
Lampe Nennleistung	0.7 W DC
Lichtstrom (Lichtquelle)	92 lm
Eingangsspannungsbereich	220mA
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP44
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Ja
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	0.12 m
Harzbeschichtung	Ja
Einbautiefe	6 mm
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.03 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Messing OT58
Farbe	Brushed nickel
Bearbeitungstyp	Elektrolytische Vernickelung + Bürstung

Oberfläche Oberfläche diffusor	
Material	Extra-helles Glas - Gehärtet
Farbe	Opal
Bearbeitungstyp	Sandstrahlen

Elektronik

99198
On/Off Driver 198~264V AC (6 - 11 art.)

99307
On/Off Driver 198~264V AC / 180~275V DC (1 - 2 art.)

99361
1-10V Controller (4 - 12 art.)

83007
On/Off Driver 198~264V AC (3 - 6 art.)

83322
Push and Simply Dim - DALI-2 Controller (4 - 11 art.)

Cables Electrification	
Cable connector	No

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Uplights - Step-Leuchten | 2 x powerLED 0.7 W DC 220 mA | CRI 90
C00478NKWXF

Single emission uplights for indoor application. The warm white LED light source with a extra wide flood light distribution is composed of 2 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 92 lm, with a 131.4 lm/W nominal luminous efficacy.

The device body is made of brass ot58 and features a brushed nickel finish, processed by means of galvanic nickel plating + brushing; the diffuser is made of extra clear glass - tempered with a sandblasting treatment.

The ingress protection degree is IP44; the total weight is of 0.03 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 0.7 W The power supply cable is included and features a 0.12 m length.

The device features protection class III and can be wall lights or floor-mounted, with a 30 mm diameter hole (in plasterboard) with an outer casing, code 84952(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	51 %
Lichtstrom (Lichtquelle)	92 lm
Leuchten Lichtstrom	47 lm
Consumption	0,7 W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B10 C0 494435h (at Tj 65 Ta 25)
L80 B10 C0 310287h (at Tj 65 Ta 25)
L90 B10 C0 147586h (at Tj 65 Ta 25)

UGR	
UGR axial	29
UGR transversal	28.6
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	91°
Light distribution simmetry	Symmetrical

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Vissa_Q | Step Lights | Accessories
C00478NKWXF

Einbaugehäuse
installationsposition: boden L=20mm, H=31mm, D=31mm.
Material:Schwarz, farbe:Black.

Code
84995

Einbaugehäuse
installationsposition: boden L=43mm, H=2mm, D=43mm.
Material:Weiß.

Code
84952

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.