

Wandleuchten - Lineare Elemente | 85-277 V | 12 x powerLEDs 15.1 W DC - 18 W AC | CRI 80
C00545AMAWW

Single emission wall lights or lines for outdoor application. The ancient white LED light source with a asymmetric wallwasher light distribution is composed of 12 powered LEDs with CCT of 2200 K and a CRI 80; the source luminous flux is 1656 lm, with a 109.7 lm/W nominal luminous efficacy.


The device body is made of aluminium alloy 6060 and features a anodised aluminium finish, processed by means of 15 µm anodizing; the diffuser is made of pmma. Surface treatment of the product body with chemical conversion of aluminum, designed to ensure maximum long-term resistance.

The ingress protection degree is IP66; the total weight is of 0.7 kg.

The total absorbed power is 18 W The power supply cable is included and features a 0.25 m length.

The device features protection class II and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse	
Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse F.	
Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	79 %
Lichtstrom (Lichtquelle)	1656 lm
Leuchten Lichtstrom	1315 lm
Consumption	18 W
Leuchten Lichtausbeute	73 lm/W
Farbtemperatur	2200 K
Standard Deviation of Colour Matching	1/16 ANSI BIN
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C
LED Life / Failure Ratio	
L70 B10 C0 214455h (at Tj 65 Ta 25)	
L80 B10 C0 136355h (at Tj 65 Ta 25)	
L90 B10 C0 67466h (at Tj 65 Ta 25)	
OPTICAL	
Optik C0/C180	90°
Light distribution simmetry	Asymmetrical

Xenia_W Pro | Lines | Accessories
C00545AMAWW



Klammer

installationsposition: wand, decke, boden L=35mm, H=72.8mm, D=36.5mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

98949



Klammer

installationsposition: wand, decke, boden L=95.6mm, H=45mm, D=28mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

89045



Klammer

installationsposition: wand, decke, boden L=155.6mm, H=45mm, D=28mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

89046



Klammer

installationsposition: wand, decke, boden L=305.6mm, H=60mm, D=28mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

89047



Blendschutz - Blendschutzblende

Blendschutzart: palpebra.

Material:Aluminiumlegierung 6060, farbe:Anodised aluminium, bearbeitungstyp :Anodisierung 20 µm.

Code

98783



Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 1,5m)

Länge 1500 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun.

Code

99216



Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 5m)

Länge 5000 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun.

Code

89190



Kabel und Stecker - Verlängerungskabel

Länge 1000 mm; isolierung doppio; kabelklemme: nein.

Code

98437

Xenia_W Pro | Lines | Accessories
C00545AMAWW



Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 5m)
Länge 5000 mm; isolierung doppio; kabelklemme: nein.

Code
98149



Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 10m)
Länge 10000 mm; isolierung doppio; kabelklemme: nein.

Code
89188




Klammer
installationsposition: wand, decke L=52mm, H=43mm, D=75mm.
Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code
C-F400006



2X



Klammer
installationsposition: wand L=32mm, H=23mm, D=25mm.
Material:Stahl AISI 304, farbe:Stahl.

Code
C-F400008