

Wandleuchten - Lineare Elemente | 198-264 V | 24 x powerLEDs 31.8 W DC - 35.4 W AC |
CRI 80
C00547AMWWW

Single emission wall lights or lines for outdoor application. The warm white LED light source with a asymmetric wallwasher light distribution is composed of 24 powered LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4320 lm, with a 135.8 lm/W nominal luminous efficacy.


The device body is made of aluminium alloy 6060 and features a anodised aluminium finish, processed by means of 15 µm anodizing; the diffuser is made of pmma. Surface treatment of the product body with chemical conversion of aluminum, designed to ensure maximum long-term resistance.

The ingress protection degree is IP66; the total weight is of 1.3 kg.

The total absorbed power is 35.4 W The power supply cable is included and features a 0.25 m length.

The device features protection class II and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse	
Dieses Produkt enthält 4 Lichtquellen der Energieeffizienzklasse D.	
Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	79 %
Lichtstrom (Lichtquelle)	4320 lm
Leuchten Lichtstrom	3432 lm
Consumption	35.4 W
Leuchten Lichtausbeute	96 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	1.5 Step
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C
LED Life / Failure Ratio	
L70 B10 C0 1240219h (at Tj 65 Ta 25)	
L80 B10 C0 745627h (at Tj 65 Ta 25)	
L90 B10 C0 309367h (at Tj 65 Ta 25)	
OPTICAL	
Optik C0/C180	90°
Light distribution simmetry	Asymmetrical

Xenia_W Pro | Lines | Accessories
C00547AMWWW



Klammer

installationsposition: wand, decke, boden L=35mm, H=72.8mm, D=36.5mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

98949



Klammer

installationsposition: wand, decke, boden L=95.6mm, H=45mm, D=28mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

89045



Klammer

installationsposition: wand, decke, boden L=155.6mm, H=45mm, D=28mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

89046



Klammer

installationsposition: wand, decke, boden L=305.6mm, H=60mm, D=28mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

89047



Blendschutz - Blendschutzblende

Blendschutzart: palpebra.

Material:Aluminiumlegierung 6060, farbe:Anodised aluminium, bearbeitungstyp :Anodisierung 20 µm.

Code

98785



Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 1,5m)

Länge 1500 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun.

Code

99216



Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 5m)

Länge 5000 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun.

Code

89190



Kabel und Stecker - Verlängerungskabel

Länge 1000 mm; isolierung doppio; kabelklemme: nein.

Code

98437

Xenia_W Pro | Lines | Accessories
C00547AMWWW




Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 5m)
Länge 5000 mm; isolierung doppio; kabelklemme: nein.

Code
98149



Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 10m)
Länge 10000 mm; isolierung doppio; kabelklemme: nein.

Code
89188




Klammer
installationsposition: wand, decke L=52mm, H=43mm, D=75mm.
Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code
C-F400006



2X



Klammer
installationsposition: wand L=32mm, H=23mm, D=25mm.
Material:Stahl AISI 304, farbe:Stahl.

Code
C-F400008