

Wandleuchten - Lineare Elemente | 100-265 V | 12 x powerLEDs 15.1 W DC - 18 W AC |
CRI 80
C00550AMWFL

Single emission wall lights or lines for outdoor application. The warm white LED light source is composed of 12 powered LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 2328 lm, with a 154.2 lm/W nominal luminous efficacy.



The device body is made of aluminium alloy 6060 and features a anodised aluminium finish, processed by means of 15 µm anodizing; the diffuser is made of pmma. Surface treatment of the product body with chemical conversion of aluminum, designed to ensure maximum long-term resistance.

The ingress protection degree is IP66; the total weight is of 0.7 kg.

The total absorbed power is 18 W The power supply cable is included and features a 0.25 m length.

The device features protection class II and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse

Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	69 %
Lichtstrom (Lichtquelle)	2328 lm
Leuchten Lichtstrom	1623 lm
Consumption	18 W
Leuchten Lichtausbeute	90 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	1.5 Step
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 1240219h (at Tj 65 Ta 25)

L80 B10 C0 745627h (at Tj 65 Ta 25)

L90 B10 C0 309367h (at Tj 65 Ta 25)

UGR

UGR axial	20.2
UGR transversal	20.6
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C0/C180	29°
Light distribution simmetry	Symmetrical

Xenia_W Pro | Lines | Accessories
C00550AMWFL



Klammer

installationsposition: wand, decke, boden L=35mm, H=72.8mm, D=36.5mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

98949



Klammer

installationsposition: wand, decke, boden L=95.6mm, H=45mm, D=28mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

89045



Klammer

installationsposition: wand, decke, boden L=155.6mm, H=45mm, D=28mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

89046



Klammer

installationsposition: wand, decke, boden L=305.6mm, H=60mm, D=28mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

89047



Blendschutz - Blendschutzblende

Blendschutzart: palpebra.

Material:Aluminiumlegierung 6060, farbe:Anodised aluminium, bearbeitungstyp :Anodisierung 20 µm.

Code

98783



Klammer

installationsposition: wand, decke L=52mm, H=43mm, D=75mm.

Material:Stahl AISI 304, farbe:Scotch Brite Stahl.

Code

C-F400006



Kabel und Stecker

Typ Kabel power + signal cable allinone; Länge 1500 mm; isolierung doppio con schermatura per segnale.

Code

C-W200020



Kabel und Stecker

Typ Kabel power + signal cable allinone; Länge 5000 mm; isolierung doppio con schermatura per segnale.

Code

C-W200021

Xenia_W Pro | Lines | Accessories
C00550AMWFL



Kabel und Stecker
Typ Kabel power + signal cable allinone; Länge 500 mm; isolierung doppio con schermatura per segnale.

Code
C-W200022



Kabel und Stecker
Typ Kabel power + signal cable allinone; Länge 1500 mm; isolierung doppio con schermatura per segnale.

Code
C-W200023




Kabel und Stecker
Länge 5000 mm; querschnitt 1.3 mm²; kabelklemme: nein; farben: schwarz - blau - braun - gelb-grün.

Code
83200



2X



Klammer
installationsposition: wand L=32mm, H=23mm, D=25mm.
Material:Stahl AISI 304, farbe:Stahl.

Code
C-F400008