

| CRI 80
C00573AMADI

Single emission lines for outdoor application. The ancient white LED light source with a diffused light distribution is composed of 144 top led LEDs with CCT of 2200 K and a CRI 80; the source luminous flux is 630 lm, with a 140.0 lm/W nominal luminous efficacy.



The device body is made of aluminium alloy 6060 and features a anodised aluminium finish, processed by means of 15 µm anodizing; the diffuser is made of glass - tempered with a anti-slip painting treatment. Surface treatment of the product body with chemical conversion of aluminum, designed to ensure maximum long term resistance.

The ingress protection degree is IP68; the total weight is of 1.535 kg.

The total absorbed power is 5.5 W The power supply cable is included and features a 0.25 m length.

The device features protection class II and can be floor-mounted with an outer casing, code 99914(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse	
Dieses Produkt enthält 3 Lichtquellen der Energieeffizienzklasse E.	




Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	27 %
Lichtstrom (Lichtquelle)	630 lm
Leuchten Lichtstrom	173 lm
Consumption	5.5 W
Leuchten Lichtausbeute	31 lm/W
Farbtemperatur	2200 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio	
L70 B10 C0 494435h (at Tj 65 Ta 25)	
L80 B10 C0 310287h (at Tj 65 Ta 25)	
L90 B10 C0 147586h (at Tj 65 Ta 25)	

UGR	
UGR axial	20.6
UGR transversal	21.3
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	98°
Optik C0/C180	107°
Light distribution simmetry	Symmetrical 2 assis

Xenia_AL | Lines | Accessories
C00573AMADI

	Federn für den Einbau	Code 99818
	Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 1,5m) Länge 1500 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun.	Code 99216
	Kabel und Stecker - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 5m) Länge 5000 mm; isolierung doppio; kabelklemme: nein; farben: weiß - schwarz - blau - braun.	Code 89190
	Kabel und Stecker - Verlängerungskabel Länge 1000 mm; isolierung doppio; kabelklemme: nein.	Code 98437
	Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 5m) Länge 5000 mm; isolierung doppio; kabelklemme: nein.	Code 98149
	Kabel und Stecker - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 10m) Länge 10000 mm; isolierung doppio; kabelklemme: nein.	Code 89188
 	Einbaugehäuse installationsposition: boden; typ installation: mauerwerk L=919mm, H=78.7mm, D=71.1mm	Code 99914
 	Endkappe - Endkappen für Xenia - 2 Stück Material:Aluminium, farbe:Grau, bearbeitungstyp :Lackierung.	Code 83188

Xenia_AL | Lines | Accessories
C00573AMADI



Schlüssel - Zubehör zur Demontage der Leuchte Xenia (2 Stück)
Material:Stahl AISI 304, farbe:Stahl.

Code
C-V500001