Lineare Elemente | 190-265 V AC /180-275 V DC
12 x powerLEDs 14.8 W DC - 18 W AC | CRI 80
C00676AMMML







Technische Daten	
Typ	Frame
Installationsposition	Boden
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	powerLEDs
Optik	Medium Flood
Light emission direction	upward
Lampe Nennleistung	14.8 W DC
Gesamtleistung	18 W
Lichtstrom (Lichtquelle)	2172 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	190 - 265 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	2700 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP68
Installationsbeschränkung	Nicht für Einsatz unter Wasser
IK	IK08
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	DALI-2
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Ja
Überrollbarkeit	2000 Kg
Einschließlich Kabel	Ja
Kabellänge	0.25 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	1.02 Kg
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	2 KV
Optiktechnologie	MicroLouvre

Oberfläche Oberfläche Gehäuse	
Material	Aluminiumlegierung 6060
Farbe	Anodised aluminium
Bearbeitungstyp	Anodisierung 15 µm

Oberfläche Oberfläche diffusor	
Material	Extra-helles Glas - Gehärtet
Farbe	Transparent
Bearbeitungstyp	Siebdruck

Cables Electrification	
IP (locked condition)	67
Cable connector	Female Socket 4 Pin M12
Cable connector	Male Plug 4 pin M12
IP (locked condition)	67

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Lineare Elemente | 190-265 V AC /180-275 V DC | 12 x powerLEDs 14.8 W DC - 18 W AC | CRI 80

C00676AMMML

Single emission lines for outdoor application. The super warm white LED light source is composed of 12 powerled LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 2172 lm, with a 146.8 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a anodised aluminium finish, processed by means of 15 µm anodizing; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. Surface treatment of the product body with chemical conversion of aluminum, designed to ensure maximum long?term resistance.

The ingress protection degree is IP68; the total weight is of 1.02 kg.

The total absorbed power is 18 W The power supply cable is included and features a 0.25 m length.

The device features protection class II and can be floor-mounted with an outer casing, code 99913(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	43 %
Lichtstrom (Lichtquelle)	2172 lm
Leuchten Lichtstrom	940 lm
Consumption	18 W
Leuchten Lichtausbeute	52 lm/W
Farbtemperatur	2700 K
Standard Deviation of Colour Matching	1.5 Step
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 1240219h (at Tj 65 Ta 25)
L80 B10 C0 745627h (at Tj 65 Ta 25)
L90 B10 C0 309367h (at Tj 65 Ta 25)

OPTICAL	
Optik C0/C180	34°
Light distribution simmetry	Asymmetrical





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Xenia_A PRO Micro Louvre | Lines | Accessories
C00676AMMML



Federern für den Einbau

Code
99818





Einbaugehäuse
installationsposition: boden; typ installation: mauerwerk L=619mm, H=78.7mm, D=71.1mm

Code
99913





Endkappe - Endkappen für Xenia - 2 Stück
Material:Aluminium, farbe:Grau, bearbeitungstyp :Lackierung.

Code
83188



Kabel und Stecker
Typ Kabel power + signal cable allinone; Länge 1500 mm; isolierung doppio con schermatura per segnale.

Code
C-W200020



Kabel und Stecker
Typ Kabel power + signal cable allinone; Länge 5000 mm; isolierung doppio con schermatura per segnale.

Code
C-W200021



Kabel und Stecker
Typ Kabel power + signal cable allinone; Länge 500 mm; isolierung doppio con schermatura per segnale.

Code
C-W200022



Kabel und Stecker
Typ Kabel power + signal cable allinone; Länge 1500 mm; isolierung doppio con schermatura per segnale.

Code
C-W200023



Kabel und Stecker
Länge 5000 mm; querschnitt 1.3 mm²; kabelklemme: nein; farben: schwarz - blau - braun - gelb-grün.

Code
83200

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Xenia_A PRO Micro Louvre | Lines | Accessories
C00676AMMML

2x 

Schlüssel - Zubehör zur Demontage der Leuchte Xenia (2 Stück)
Material:Stahl AISI 304, farbe:Stahl.

Code
C-V500001

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.